

Electric inflator pumps

Electric inflator for dinghies and SUP boards

2-stage pump for inflation and deflation.
Compact and easy to carry by means of a comfortable handle.
Digital controller and LCD display for pressure setting.
Lighter plug + battery clamps.

Code	Function	V	W	Flow l/min	Max pressure	Current draw A	mm
66.451.01	Inflation + deflation	12	110	350 at low pressure 70 at high pressure	1380 mbar (20 PSI)	9-12	155x250x175



OSCULATI



GE BP-1 12V inflator

Automatic stop when the adjustable preset pressure is reached.
With a flow of **160 l/min**, it inflates at a max pressure of **1200 mbar (18 psi)**.
The hose/inflator screw-type connector is stable and safe.
It comes in a shoulder carrying bag with all accessories: 1.7-m hose, 3-m power cable, lighter plug and 12V battery clamps.
The standard version with bayonet fitting is ideal for **SUP** boards.

Code	Functions	V	W	Flow l/min	Max pressure	Current draw A	mm	OPTIONAL connections
66.449.11	Inflation	12	240	160	1200 mbar (18 PSI)	13	205x105x130	66.449.12

66.449.12 The spares kit includes an additional hose and several fittings to inflate kits, dinghies, liferafts, air mattresses and pool inflatables.



New

GE BTP-2 inflator

An evolution of the previous model, this inflator reaches a 1.2-bar (18 psi) pressure and is ideal for SUP boards.
Automatic stop when the preset pressure, adjustable by means of a pressure gauge, is reached.
Fitted with hose and bayonet connector, universal fitting kit, 2.5-m power cable and battery terminal pliers.
It comes in a convenient and sturdy shoulder bag.
Average inflating time: 9'30" (265-litre SUP @ 1250 mbar).

Code	Functions	V	W	Flow l/min	Max pressure	Current draw A	mm	kg
66.449.13	Inflation+ deflation	12	240	120 - 420	1,2 bar (18PSI)	18	295x105x160	2.5



GE 10-8 and GE 10-B electric inflator

High-pressure, low consumption inflators ideal for inflatable bottom dinghies, kites and kayaks needing elevated pressure.

Designed to further optimize the performance, the efficiency and the reliability of BST inflators.

Specification:

- New electronic card for better precision when operating the inflator.
- New pressure sensors for 3-8mbar accuracy.
- State and troubleshooting LEDs for the inflator and the power supply.
- Modified position of the pressure switch for easier user.
- For GE 10-B version: new 12V 9Ah battery with universal battery charger INCLUDED.

Code	Functions	V	W	Flow l/min	Max pressure	Current draw A	mm	Rechargeable battery
66.447.12	Inflates+deflates	12	156	450	800 mbar (11.6 PSI)	13	180x200x240	No
66.447.13	Inflates+deflates	12	156	450	800 mbar (11.6 PSI)	13	180x200x240	Yes

66.447.22 220V/120V charger for GE 10-B inflator code 66.447.13; also suitable for BST800BAT old model code 66.447.11.



SCOPREGA
look beyond



▲ 66.447.12