

NAVISAFE portable Navigation lights

NAVISAFE 

Multifunctional Navigation lights, battery powered (3 x AAA), waterproof (IP68), submersible to 20 m, float light facing up, US Coast Guard approved for 2 nautical miles, superbright LEDs. Various mounting solutions available - magnet, suction cup and bayonet (Navimount).

NAVISAFE Navilight 360° All-round white light 2NM

5 operating modes: All-round/Anchor light (360°, 15hrs. burn time), Masthead light (225°, 24hrs. burn time), Sternlight (135°, 32hrs. burn time), Safety/Flashing light (360°, 85hrs. burn time), Cabin/Courtesy light (72hrs. burn time). Dimensions: Ø68x35h-90mm (depending on model).

Code	Model
11.139.01	with magnetic base, straps and lanyards for multiple fixing and securing
11.139.04	with bayonet base (Navimount), base compatible with GoPro® camera mounts
11.139.06	with suction cup base, base compatible with GoPro® camera mounts



NAVISAFE Navilight Tricolour 2NM

5 operating modes: tricolor masthead light (135° white, 112.5° red, 112.5° green, 12h life), stern light (135°, 32h life), bicolour light (112.5° red, 112.5° green, 20h life), green light (112.5°, 38h life), red light (112.5°, 38h life). Dimensions: 68x35/90(h) mm depending on the model.

Code	Model
11.139.03	with magnetic base, straps and lanyards for multiple fixing and securing
11.139.05	with bayonet base (Navimount), base compatible with GoPro® camera mounts
11.139.07	with suction cup base, base compatible with GoPro® camera mounts



NAVISAFE mounting kit + pole + 360° light

Complete solution for small tenders, canoes, fishing boats that need a 360° white light.

Code	It contains
11.139.19	Navilight 360° 11.139.01; 4-pc pole; vertical support; neoprene carrying bag



NAVISAFE bracket for 25-mm Ø tube

11.139.33 Magnetic head to house 11.139.01/03/04/05.



NAVIMOUNT mounting system

For NAVISAFE Navilight 11.139.04 and 11.139.05.

Code	Description
11.139.11	horizontal support
11.139.12	horizontal support with self-adhesive rubber base for pneumatic boats
11.139.13	boats support for 25 or 35 mm rails

