




▲ 13.478.01



FORESTI E SUARDI Circinus LED courtesy light for recess mounting

IP67

Electro-plated brass body, clear technopolymer diffuser. Suitable for mounting on flammable surfaces. Fastening by means of threaded finish ring.

Code	V	W	Lumen	K	LED beam angle	No of LEDs	Light colour	←→ mm		
								recess Ø	outer Ø	overhang
13.478.01	12/24	0.24	20	6000	60°	1	White	25	32	2
13.478.03	12/24	0.24	6	-	60°	1	Blue	25	32	2



FORESTI E SUARDI Elettra-t LED courtesy light, recessless version

IP67

FLUSH MOUNT

Clear technopolymer body, electro-plated technopolymer snap finish ring. Suitable for mounting on flammable surfaces both horizontally and vertically. Innovative design, Wall Washer light effects. Screw mounting.

Code	V	W	Lumen	K	LED beam angle	No of LEDs	Light colour	←→ mm	
								recess Ø	overhang
13.479.60	12/24	0.48	40	4000	60°x10°	1 SMD LED	White	38x31x10	
13.479.61	12/24	0.48	12	-	60°x10°	1 SMD LED	Blue	38x31x10	

LED courtesy light for recess mounting - frontal orientation

IP55

Translucent polycarbonate body. Stainless steel finish ring. Suitable to light up steps.

Code	Finish	V	W	lumen	LED beam angle	No of LEDs	Light colour	←→ mm		
								recess Ø	outside Ø	overhang
13.181.00	no finish ring	12	0.6	12	24°	3 LED Long Life	yellow	28	46.3x23.3	2.4
13.181.01	mirror-polished	12	0.6	12	24°	3 LED Long Life	yellow	28	46.3x23.3	2.4
13.181.03	mirror-polished	12	0.6	7	20°	3 LED Long Life	blue	28	46.3x23.3	2.4

LED courtesy light for recess mounting - frontal orientation

IP67

Polycarbonate body and mirror-polished stainless steel front panel.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	←→ mm		
								recess Ø	outside Ø	overhang
13.180.01	12	0.2	36	5000	100°	3 LED Long Life	white	44x16	29x84	3.5
13.180.03	12	0.2	14	-	100°	3 LED Long Life	blue	44x16	29x84	3.5

LED courtesy light, recessless version - frontal orientation

IP67

FLUSH MOUNT

Mirror-polished stainless steel front panel.

Code	V	W	Lumen	K	LED beam angle	No of LEDs	Light colour	←→ mm	
								outside	overhang
13.178.04	12	1.2	83	5500/6300	120°	6	White	72.5x38	10.5
13.178.03	12	1.2	22	-	120°	6	Blue	72.5x38	10.5

Oculus ultra-flat courtesy light - frontal orientation

IP67

Recessless mounting, 5-mm thick. Watertight technopolymer body with polished stainless steel finishing ring.


Code	Model	V	W	Lumen	K	LED beam angle	No of LEDs	Light colour	←→ mm	
									outside	overhang
13.178.10	Front light, SS ring	12	0.3	30	3000	100°	3	White	80x37x5	
13.178.14	Perimeter light, SS front panel	12	0.3	30	3000	360°	3	White	78.4x35.4x5	
13.178.11	Front light, SS ring	12	0.3	10	-	100°	3	Blue	80x37x5	
13.178.15	Perimeter light, SS front panel	12	0.3	10	-	360°	3	Blue	78.4x35.4x5	




▲ 13.181.00



▲ 13.181.01




▲ 13.181.03




▲ 13.178.10/11



▲ 13.178.14/15



▲ 13.178.10/11



▲ 13.178.14/15



▲ 13.178.xx