

Classic electrical spot light made of stainless steel

OSCULATI

IP67

Mirror-polished stainless steel body. 100% watertight. 350° horizontal and 55° vertical rotation. Two speeds. 100W + 90W H4 halogen double-filament bulb (spot + flood).

It can be connected to 3 optional controls (independent or combined) for the desired configuration:
1) Joystick-operated bridge control (to be connected to the lighthouse via a phone cable), 4.5-m cable included, 10-m cable to be purchased separately.
2) Wireless bridge control (power the panel and it will interface wireless to the lighthouse).
3) Traditional radio remote control with bracket for mounting on the bridge.



▲ 13.225.39



▲ 13.225.41/42






▲ 13.225.40



Code	V	CD candles*	W	Range 0.25 Lux*	OPTIONAL joystick control	OPTIONAL bridge wireless control	OPTIONAL wireless remote control	OPTIONAL 10-m extension cable for 13.225.39	Spare bulb
13.229.12	12	135.000	100/90	775	13.225.39	13.225.41	13.225.40	13.225.31	13.225.35
13.229.24	24	135.000	100/90	775	13.225.39	13.225.42	13.225.40	13.225.31	13.225.36

* To be measured at the centre of the light beam.



LED electric exterior spotlight

OSCULATI

Body: diecast aluminium coated in white high-resistance and anti-corrosion resins. 100% watertight. 2-speed 355° horizontal rotation. 50° vertical rotation. CREE high-quality LED unit. 54W consumption corresponding to a traditional 100 W bulb.

It can be connected to 3 optional controls (independent or combined) for the desired configuration:
1) Joystick-operated bridge control (to be connected to the spotlight via a phone cable), 4.5-m cable included, 10-m cable to be purchased separately.
2) Wireless bridge control (power the panel and it will interface wireless to the spotlight).
3) Traditional radio remote control with bracket for mounting on the bridge.



▲ 13.226.39



▲ 13.226.41





▲ 13.226.40



Code	V	CD candles*	W	K	Lumen	No of LEDs	LED beam angle	Range 0.25 Lux*	OPTIONAL joystick control	OPTIONAL wireless remote control	OPTIONAL bridge wireless control	OPTIONAL 10-m extension cable for 13.226.39
13.226.12	12	132.000	54	6000	6000	18	9°	726	13.226.39	13.226.40	13.226.41	13.225.31
13.226.24	24	132.000	54	6000	6000	18	9°	726	13.226.39	13.226.40	13.226.42	13.225.31

* To be measured at the centre of the light beam.



SANSHIN swivelling light with electric control

Fitted with two 55W halogen bulbs. Light alloy white body, remote control, clamp flasher and lantern variable rotation speed. Max capacity 1200m, dimensions 200x232mm.

Code	V	Candles CD	Current draw A	Spare bulb	Spare panels	Second station panels	kg
13.343.12	12	200.000	10	13.343.01	13.343.22	13.344.12	6
13.343.24	24	160.000	6	13.343.02	13.343.34	13.344.24	6

