

Lights for topsides, gangplanks and below the waterline



Pair of LED docking lights

IP65

LED

2-mode docking lights: 20°-angle, 320 mA HD LED bow light + 85°-angle 80 mA side light. The lights are wired separately. Recessless mounting. Polished AISI 316 SS body.

| Code | Description | V | Lumen | K | LED beam angle | LED | mm |
|-----------|----------------|----|---------|------|----------------|-----------|--------------|
| 13.653.00 | Docking lights | 12 | 280/125 | 6000 | 20° + 85° | 320+80 mA | 90.8x66.2x20 |



ATTWOOD bow LED light

LED

Polished stainless steel body. Totally watertight. 120° light beam. High-power LED equivalent to a 50W halogen bulb. **No recess needed.** Sold in pairs. IP68.

| Code | V | W | Lumen | LED beam angle | mm |
|-----------|----|--------|-------|----------------|-----------|
| 13.652.01 | 12 | 5 each | 750 | 120° | 114x71x30 |





Compact fairing light pair with LED bulb

AISI 316

Made of mirror-polished AISI 316 stainless steel. Front protection lens.

| Code | LED included | | Cone | Spare LED |
|-----------|--------------|-------|---------|-----------|
| 13.254.13 | 12 V | 4 W | 45° FMW | 14.258.56 |
| 13.254.14 | 24 V | 3.5 W | 45° FMW | 14.258.59 |




Fairing light pair, built-in model fitted with Sealed Beam 4" watertight bulb.

AISI 316

Made of mirror polished AISI 316 stainless steel.

| Code | Bulb included | Cone | Spare bulb |
|-----------|-----------------|---------|------------|
| 13.258.12 | 12 V - 50 W x 2 | 70°x30° | 14.249.11 |
| 13.258.24 | 24 V - 50 W x 2 | 40°x5° | 14.249.08 |




▲ 13.257.12-24



▲ 13.256.12-24

Transom light made by white ABS, 100% watertight

Fitted with Sealed Beam bulb 14.249.07/08.

To be mounted under the platform to illuminate the water surface; supplied with 1.20 m power cable.

| Code | Version | Type | Base Ø mm | Size mm |
|-----------|----------|-------------|-----------|---------|
| 13.256.12 | inclined | 12 V - 35 W | 170 | 90 |
| 13.256.24 | inclined | 24 V - 50 W | 170 | 90 |
| 13.257.12 | straight | 12 V - 35 W | 170 | 90 |
| 13.257.24 | straight | 24 V - 50 W | 170 | 90 |

