

2-pole flying plug/socket**IP68**

IP68 plug/socket micro connector.

Code	Poles	Max A	Cable section mm ²	Cable Ø mm	↔ outside mm
14.374.02	2	10	0.25-1.5	1x(3-8) / 2x(1.9-2.5)	Ø14 x 90

**2/3/4-pole flying plug/socket****IP68**

IP68 plug/socket connection.

Code	Poles	Max A	Cable section mm ²	Cable Ø mm	↔ outside mm
14.371.04	2/3/4	17.5	0.5 - 4	3x(2-4) / 4x(2-4)	Ø 23 x 113

**2/3/4-pole plug/socket for panel or bulkhead mounting****IP66**

IP66 plug/socket connection.

Code	Poles	Max A	Panel thickness mm	Cable section mm ²	Cable Ø mm	↔ outside mm
14.372.04	2/3/4	17.5	1-7	0.5 - 4	1x(4-12) 2x(2-4)	Ø 23

**Fairleads and glands****SCANSTRUT vertical cable seals****SCANSTRUT**

They assure perfect watertightness (IP-X7) for cable passing. They allow the cables to pass without disassembling possible end connectors. Edgeless shape for higher resistance and to avoid possible blocks for the line. Threaded holes for easy assembling and numberless disassemblings.

Every item is supplied with a choice of pre-bored or to-be-bored seals for the utmost easiness and flexibility of use.

Packed in convenient display Blister.

Black plastic RETAIL (1pcs)	Black plastic BULK (10pcs)	Grey plastic RETAIL (1pcs)	Grey plastic BULK (10pcs)	SS RETAIL (1pcs)	Cable Ø mm	Connector B max Ø mm	A Ø mm
-	-	14.171.02*	-	-	2-6	6	30
14.170.02	14.170.82	14.172.02	14.172.82	14.173.02	2-8	16	39
14.170.04	14.170.84	14.172.04	14.172.84	14.173.04	4-9	21	49
14.170.09	14.170.89	14.172.09	14.172.89	14.173.09	9-14	21	49
14.170.10	-	14.172.10	-	14.173.10	9-14	30	59
-	-	-	-	14.173.12	12-15	40	69

* Satin-finished version



▲ 14.171.02



▲ 14.173.xx



▲ 14.172.xx



▲ 14.170.xx