

ROKK watertight wireless battery charger

The ROKK wireless IPX6 12/24V series (Qi certified) allow recharging mobile phones and tablets by simply placing them on the charger.


Designed for marine use, they are 100% watertight.

The two outdoor version feature an excellent anti-skid and UV-resistant surface.

3 versions are available depending on the installation mode the user prefers.

Input	Dimensions	Cable
12/24 V	Ø 96 mm	30 cm

Code	Version	Description	Output W
14.515.11	Hidden	Hidden version for installation under the surface. A single anti-skid ring is visible to indicate the position	10
14.515.12	Surface	Flush version to be recessed into the cabinet	10




ROKK SUB wireless watertight battery charger with invisible integrated charging - 10W

To be installed indoors or outdoors under any non-metallic material (fiberglass, leather, PVC, fabric, wood, carbon fibre, etc.)

IPX6 watertight, compatible with any mobile phone having a non-metallic case and 3-mm minimum thickness. Qi wireless charging technology (Apple, Samsung, Huawei, etc.).

Code	Input V	Output W	mm
14.515.15	12/24	5	Ø 98 x 17



SCANSTRUT



ROKK Wireless Nano 10W watertight wireless phone charging mount

Wireless phone charging mount designed for the marine environment. For phones 56- (2.16") to 106-mm (4.17") wide.

100% IPX6 watertight.

- Safe grip securely holds your phone.

- One-handed dock/charge operation.

- Installation on any flat surface.

Code	Input V	Output W	mm	
			closed	open
14.514.12	12/24	10 (9V, 1.1 A)	80x34x72	130x34x72

SCANSTRUT



ROKK ACTIVE watertight wireless phone charging mount

High-performance wireless phone charging mount designed for marine environment. For phones 120-mm (4.7") to 173-mm (6.8") long.

- 100% IPX6 watertight.

- Self-aligning grip securely holds your phone.

- Anodized aluminium case.

- One-handed dock/charge operation.

- Installation on any flat surface.

- LED charge indicator.

Code	Input V	Output W	mm		Cable cm
			closed	open	
14.514.11	12/24	10	74x33x142	74x33x206	50



SCANSTRUT

