



ITALWINCH Orchid windlass

100% AISI316 stainless steel vertical windlass.

Fitted with built-in chain counter sensor. Recommended for boats up to 20 m.

The version with 12-mm chain can also use a 18-mm rope.

GD + gypsy	GO	Motor		Average current draw A	Ø Chain gypsy mm	Line Ø mm	Max pull kg	Breaking load kg	Line speed m/min	kg
		V	W							
02.405.01	02.405.11	12	1700	138	10	-	1650	240	12	25/35-30/40
02.405.02	02.405.12	24	1700	75	10	-	1700	250	12	25/35-30/40
02.405.03	-	24	2000	N/A	12	18/19	1700	250	12	25/35-30/40



▲ 02.405.01/02/03




▲ 02.405.11/12

ITALWINCH STAR PLUS windlass

AISI316 stainless steel body. Fitted with nickel-plated bronze gypsy + drum.

For boats up to 26 metres long. Built-in chain counter sensor.

Code	Motor		Current draw A	Ø Chain gypsy mm	Max pull kg	Working load kg	Line speed m/min	kg
	V	W						
02.406.14	24	2300	190	10	2000	900	12	80
02.406.15	24	2300	190	12	2000	900	12	80
02.406.16	24	2700	200	12	2200	1050	12	90

**ITALWINCH GIGLIO manual windlass**

Anodised Aluminium body. Chromed bronze gypsy.

Code	Ø Chain gypsy mm	Working load kg	kg
02.407.01	6	300	10,2
02.407.02	8	300	10,2

