



▲ 40.142.xx



▲ 40.142.xx



▲ 40.143.xx



▲ 40.143.xx

Pop-up cleat

AISI 316

A compact and ergonomic design solution. Made of mirror-polished **AISI316 stainless steel**. Easy to install, no recess fit required.

Code	Mounting	Length mm	Width mm	Centre distance mm	Overhang mm	Breaking load kg
40.142.01	With 6x40-mm Ø studs (included)	115	45	67	15	700
40.142.07	With 8x45-mm Ø studs (included)	143	53	92	21	1200
40.142.02	With 8x45-mm Ø studs (included)	172	65	115	22	1300
40.142.03	With 10x50-mm Ø studs (included)	210	70	137	25	1800
40.142.04	With 12x60-mm Ø studs (not included)	270	83	172	30	2600
40.142.05	With 16x80-mm Ø studs (not included)	350	104	219	36	3000
40.143.01	Screws (not included)	115	45	67	15	700
40.143.07	Screws (not included)	143	53	92	21	1200
40.143.02	Screws (not included)	172	65	115	22	1300
40.143.03	Screws (not included)	210	70	137	25	1800
40.143.04	Screws (not included)	270	83	172	30	2600



Low profile pop-up cleat

AISI 316

PATENT / BREVETTATO

A compact and ergonomic design solution. Made of mirror-polished **AISI316 stainless steel**. Easy to install, no recess fit required. US M617040 patented model

Code	Mounting	Length mm	Width mm	Centre Abstand mm	Overhang mm
40.143.10	Ø-6mm screws	115	38	67	15
40.143.12	Ø-8mm screws	166	55	115	20



Avion pop-up cleat

AISI 316

PATENT / BREVETTATO

A modern and aerodynamic design solution. Very sturdy yet low profile. Made of mirror-polished **AISI316 stainless steel**. US M617040 patented model

Code	Mounting	Length mm	Width mm	Centre distance mm	Overhang mm
40.144.01	Ø-6mm screws	115	37	67	14
40.144.02	Ø-8mm screws	166	52	115	21



Wing pop-up cleat

Made of mirror-polished **AISI316 stainless steel**. The pop-up mechanism is fitted with snap cam to avoid unwanted opening.

Code	←→ mm		Studs mm	Breaking load kg
	closed Ax B	open C x D		
40.145.01	280x46	235x44	3x12	9460
40.145.02	360x59	322x100	3x16	20120
40.145.03	480x79	431x130	3x16	24500

