

MARLOW Excel PS12 braid without cover**SPORT BOAT**

Ideal for: halyards, sheets, up/downhaul and cascade systems.

Characteristics: easy to splice when without cover. It can be spliced as leading rope on more performing ropes.

Material: 12-strand pre-stretched polyester.

Blue	Red	White	Ø mm	Breaking load kg	Weight kg/100 m	m
06.421.04BL	06.421.04RO	-	4	678	1.19	200
06.421.05BL	06.421.05RO	06.421.05BI	5	1080	1.91	200
06.421.06BL	06.421.06RO	-	6	1330	2.47	200

Marlow®**MARLOW Excel Racing braid****HIGH PERFORMANCE**

Ideal for: halyards, low-stretch sheets, reefs, multiple professional applications.

Features: floating, excellent stretch resistance, easy to splice, the cover can be removed.

Core: 12-strand Dyneema SK78.

Cover: high-strength 16-plait polyester.

Marlow®

Blue	Red	White	Black	Lime	Orange	Ø mm	Breaking load kg	Weight kg/100 m	m
06.429.15BL	06.429.15RO	-	-	06.429.15LI	-	1.5	139	0.17	100
06.429.02BL	06.429.02RO	-	-	06.429.02LI	-	2	224	0.29	100
06.429.03BL	06.429.03RO	06.429.03BI	06.429.03NE	06.429.03LI	06.429.03AR	3	463	0.58	100
06.429.04BL	06.429.04RO	06.429.04BI	06.429.04NE	06.429.04LI	06.429.04AR	4	995	1.24	100
06.429.06BL	06.429.06RO	06.429.06BI	06.429.06NE	06.429.06LI	06.429.06AR	6	2056	2.41	100

MARLOW Excel Fusion 78 braid with cover**SPORT BOAT**

Braid with cover.

Ideal for: standard sheets and spinnaker sheets.

Characteristics: very light, it doesn't absorb water, reduced elongation, easy to splice, soft to touch despite its RACING technical characteristics.

Core: pre-stretched Dyneema SK78.

Cover: pre-stretched Dyneema braided with soft polypropylene.

Marlow®

Blue	Red	Black	Ø mm	Breaking load kg	Weight kg/100 m	m
06.424.06BL	06.424.06RO	06.424.06NE	6	1088	1.7	100
06.424.08BL	06.424.08RO	06.424.08NE	8	1411	3.0	100
06.424.10BL	06.424.10RO	06.424.10NE	10	2472	4.4	100

MARLOW D12 braid without cover**HIGH PERFORMANCE**

Braid without cover.

Ideal for: halyards, backstays, vang, tackles, all dynamic applications.

Features: floating, lightweight, stretch resistant, top quality, quick and easy to splice, it doesn't absorb water, UV- and abrasion- resistant Marlow ArmourCoat.

Material: 12-strand Dyneema SK78 with anti-abrasion Marlow ArmourCoat.

Marlow®

Fleck colour				Ø mm	Breaking load kg	Weight kg/100 m	m
Blue	Black	Red	White				
06.426.25BL	06.426.25NE	06.426.25RO	-	2.5	569	0.37	200
06.426.30BL	06.426.30NE	06.426.30RO	-	3	995	0.53	200
06.426.40BL	06.426.40NE	06.426.40RO	06.426.40BI	4	2060	0.98	200
06.426.50BL	06.426.50NE	06.426.50RO	06.426.50BI	5	2360	1.28	200
-	06.426.60NE	06.426.60RO	06.426.60BI	6	3490	1.77	200
-	06.426.80NE	-	-	8	6330	5.70	200
-	06.426.10NE	-	-	10	9274	8.35	100

MARLOW Formuline Wind Surf Racing braid**WIND SURF**

12-strand Dyneema SK75 braid to adjust the surf sail.

Extremely light and resistant, it doesn't add unnecessary weight to the sails.

White	Black	Ø mm	Breaking load kg	Weight kg/100 m	m
06.422.04	06.422.04NE	3.8	619	0.89	100

Marlow®