

Crosslinked polyethylene fuel tanks for petrol

OSCOLATI



Made in compliance with ISO 21487. RINA CE certified. Fitted with brass tap plug, float protection and shock-absorbing floating protection where necessary.

Code	Capacity l	Fuel	Length mm	Max length for float cm	Vent Ø mm	Inlet plug Ø mm	Tap plug Ø inches
52.035.09	62	petrol	660x535x245 (+60) h	25	16 built-in	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.10	90	petrol	1060x535x221 (+43) h	20	16 built-in	38-50	90° elbow, 3/8" female thread
52.035.11	116	petrol	1360x535x221 (+43) h	20	16 built-in	38-50	90° elbow, 3/8" female thread
52.035.01	142	petrol	1150x470x300 (+83) h	26	16 hose adaptor	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.03	189	petrol	900x850x340 (+55) h	26	16 hose adaptor	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.04	239	petrol	1200x640x370 (+50) h	30	18/16 built-in	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.05	206	petrol	1100x1000x265 (+60) h	17	16 hose adaptor	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.06	198	petrol	1200x640x310 (+50) h	25	18/16 built-in	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.035.07	353	petrol/ diesel	1000x870x581 (+43) h	49	16 built-in	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.036.05	347	petrol	1450x930x335 (+50) h	28	19 built-in	38	90° elbow, 3/8" female thread + preset for 2nd tap plug
52.039.08	315	petrol/ diesel	1340x660x450 (+50) h	41	19 built-in	38-50	90° elbow, 3/8" female thread + preset for 2nd tap plug

52.035.96 Additional tap plug OPTIONAL

