



MARLOW soft shackles

MARLOW soft shackles

Made with a 12-strand high-strength braid without cover. In comparison with traditional steel shackles, fabric shackles offer excellent pull under load with reduced weight and are easier to release when no load is applied. To be used to fix sheets, halyards, blocks and rigging in general.

Code	Ø mm	Breaking load kg		Length mm
08.300.03	3	1000	8	150
08.300.04	4	2000	10	170
08.300.05	5	2250	16	160
08.300.06	6	4500	24	300
08.300.08	8	8700	60	450

The length indicated refers to the soft shackle when open.

Soft shackle

Soft shackles are hand-made with a Marlow D12 Dyneema SK78 line without cover. In comparison with traditional steel shackles, fabric shackles offer excellent pull with reduced weight. Available color: black.

Code	Ø mm	Breaking load kg		Length mm	 ORDER BY BOX
08.310.04	4	2370	5.5	200	2
08.310.06	6	4010	9	300	2
08.310.07	7	6160	14.9	350	2
08.310.09	9	7980	27.4	450	2

The length indicated refers to the soft shackle when open.

OSCULATI



Marlow®



Shackles

OSCULATI

Galvanised steel D-Shackles

Fine finish and high quality threads, heavy galvanization.

Code	Pin mm	Ø D mm	A mm	L mm	Working load kg	Breaking load kg	 ORDER BY BOX
08.320.05	5	5	10	20	80	320	10
08.320.06	6	6	13	25	100	400	10
08.320.08	8	8	16	32	200	800	10
08.320.10	10	10	19	38	320	1280	10
08.320.12	12	12	25	51	520	2080	10
08.320.14	14	14	28	58	800	3200	-
08.320.16	16	16	32	64	1100	4400	-
08.320.20	20	20	38	76	1500	6000	-
08.320.25	25	25	51	100	2100	8400	-

Galvanized lyre shackle

Its shape makes it deal to be used with thimbles.

Code	Pin mm	Ø D mm	A mm	L mm	Working load kg	Breaking load kg	 ORDER BY BOX
08.329.06	6	6	13	25	100	400	20
08.329.08	8	8	16	32	200	800	10
08.329.10	10	10	19	38	320	1280	10
08.329.12	12	12	25	51	520	2080	-
08.329.14	14	14	28	58	800	3200	-
08.329.16	16	16	32	64	1100	4400	-
08.329.20	20	20	38	76	1500	6000	-
08.329.25	25	25	51	100	2100	8400	-

