

VIADANA micro-block

Made of nylon and AISI316 stainless steel.

Code	Version	Sheave Ø mm	Max height mm	Breaking load kg	Working load kg	For ropes mm
55.250.01	Single with fixed head	22	34	700	100	4/6
55.250.02	Single with becket	22	34	700	100	4/6
55.250.03	With swivel toggle head	22	34	450	50	4/6
55.250.04	Footblock (2 fixing bores)	22	34	700	100	4/6



VIADANA composite material ball bearing ratchet block for winches

With stainless steel ball bearings + ratchet. 57-mm Ø sheave, 10-mm max Ø sheet, 900-kg breaking load, 205-kg working load.

Code	Version	Sheave Ø mm	Breaking load kg	Working load kg	Sheet max Ø mm
55.408.00	Single, clockwise rotation	57	900	205	10
55.408.01	Single, anti-clockwise rotation	57	900	205	10



HYE blocks for sailing dinghies



TUFNOL HYE block

Technical Specifications			
Version	For ropes mm	Ø puleggia tufnol mm	Breaking load kg
A	8	30	800
B	10	35	1000
C	12	43	1500
D	14	50	2000
E	16	60	2500

Model	A	B	C	D	E
1 pulley, attachment fixed (EO)	55.001.00	55.001.01	55.001.02	55.001.03	-
Single with fixed head (EB)	55.002.00	55.002.01	55.002.02	55.002.03	55.002.04
Single with swivel head (EW)	55.003.00	55.003.01	55.003.02	55.003.03	55.003.04
Single with becket and fixed head (EBH)	55.005.00	55.005.01	55.005.02	-	-
Double with fixed head (TB)	55.006.00	55.006.01	55.006.02	55.006.03	55.006.04
Double with swivel head (TW)	55.007.00	55.007.01	55.007.02	55.007.03	55.007.04
Double with becket and fixed head (TBH)	55.008.00	55.008.01	55.008.02	55.008.03	-
Single with becket and swivel head (EWH)	55.010.00	55.010.01	55.010.02	-	-
Fiddle with swivel head (ZBW)	55.011.00	55.011.01	55.011.02	-	-
Single footblock (3-screw mounting) (LB)	55.012.00	55.012.01	55.012.02	55.012.03	55.012.04
Fiddle with becket and cam (ZBK)	56.101.08	56.101.10	56.101.12	-	-

