

Universal winch handle holder

Made of **black nylon**, suitable for winch handles; 3-screw mounting, used instead of PVC pockets.


| Code | Base Ø mm | Overhang mm |
|-----------|-----------|-------------|
| 57.635.70 | 52 | 26 |



Jib furlers and spreader covers

Self-adjusting spreader boots with aerodynamic profile

Made of soft thermoplastic, designed for round- and wing-section crosstrees. Fast to mount by means of our self-amalgamating tape 65.115.01 or similar.

| Code | For cables up to mm | For crosstrees, max section mm | External dimensions mm |  ORDER BY BOX |
|-----------|---------------------|--------------------------------|------------------------|--|
| 57.492.01 | 4 | 38x13 | 114x45x48 | 2 |
| 57.492.02 | 6 | 57x17 | 145x65x60 | 2 |
| 57.492.03 | 8 | 83x25 | 190x93x71 | 2 |



OSCULATI



Self amalgamating tape for spreader boots

Made of soft UV-resistant plastic material; easy to remove when worn out.

| Code | Colour | Roll |
|-----------|--|--------------|
| 57.374.00 |  light grey | 25 mm x 10 m |


PSP
marine tapes



“Sailguard” sail savers

Made of **white nylon**; easily installed **without dismantling the shrouds**; supplied in an elegant package.


| Code |  ORDER BY BOX | Suitable for |
|-----------|--|------------------|
| 57.373.40 | 2 | stays up to 9 mm |



Sea Sure jib furling system with manual return line

Made of **stainless steel**, fitted with **nylon** pulley. Designed to guarantee full reliability. The drum is closed and protected thus avoiding the line from getting stuck or twisting when opening and closing. It consists of stainless steel bearings for perfect functioning even when the forestay is under maximum tension. It is only 50-mm high thus allowing to install the jib very low, just above the deck in order for the sail to be fully efficient. It can also be mounted below deck by using an additional stainless steel extension hose. The jib furling system can wind up to 3.5 mm of 3-mm diameter line thus allowing the use of sails with approx. 3-mm long lower rim (length from tack to sheet). This length is shorter in case of lines with larger diameter.

| Code | Suitable for | Ø Drum mm |  |
|-----------|--------------------|-----------|---|
| 57.299.00 | All types of keels | 69 | 116 |



Sea Sure swivel

| Code | Description |
|-----------|---|
| 57.295.00 | Made of stainless steel, for furler, integrated stainless steel bearing |

