


SIKAFLEX® products



Sikasil® C silicone sealant

SILICON

Multipurpose, mono-component, neutral, non-corrosive sealant. No primer needed, it adheres to most of the construction materials: metals, cement, painted surfaces, wood, plastic, ceramic and glass tiles. For a water-tight, elastic and flexible sealing result. Resistant to UV rays, fungi and mould. For indoor and outdoor applications. Operating temperature: -40 °C min. / +150 °C max.



Code	Cartridge of ml	Colour	€ PACKAGE
65.418.01	300	☐ white	12
65.418.02	300	☒ Black	12
65.418.03	300	☐ grey	12
65.418.04	300	- Transparent	12

Polymer sealant SIKAFLEX 591

This sealant uses the STP-Silane Terminated Polymers technology. It is suitable for elastic vibration-resistant gluing and for a wide range of indoor and outdoor sealing applications. Isocyanate, solvent, PVC, phthalate and tin catalyst free product.



Code	Package	Colour	€ PACKAGE
65.288.38	70-ml self-extruding tube	☐ white	24
65.288.39	70-ml self-extruding tube	☒ Black	24
65.288.01	300-ml cartridge	☐ white	12
65.288.02	300-ml cartridge	☒ Black	12
65.288.03	300-ml cartridge	☐ grey	12
65.288.06	600-ml bag	☐ white	20

Spreadable adhesive SIKAFLEX 292i

For elastic and resistant bonding. Uses: bonding between hull and superstructures or decks, bonding of keels, handrails, bonding of bulkheads (sandwich panels).



Code	Package	Colour	€ PACKAGE
65.289.05	310-ml cartridge	☐ white	12
65.289.04	600-ml bag	☐ white	20