

OSCULATI antifouling paints

For professional use



SP Classic 153 antifouling paint

Self-polishing antifouling paint based on copper salt free organic biocide. Compatible with any hull (fibreglass, aluminium, wood, etc.). Yield: 9 m²/l. Recommended for moderately aggressive weather conditions.

Minimum temperature of application 10° C. Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

EU Regulation 2020/1182.

white	blue	Black	Package I	PACKAGE
65.601.11*	65.601.12	65.601.13	0.75	6
65.601.21*	65.601.22	65.601.23	2.5	2
-	65.601.32	65.601.33	5	1

* Restricted use for professional users.

OSCULATI



HM Classic 153 antifouling paint

Hard matrix antifouling paint based on copper salt free organic biocide. Compatible with any hull (fibreglass, aluminium, wood, etc.). Yield: 9 m²/l, colour 7 m²/l. Recommended for aggressive areas in the average. Minimum temperature of application 10° C. Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

Minimum temperature of application 10° C. Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

EU Regulation 2020/1182.

white	blue	Black	Package I	PACKAGE
65.611.11	65.611.12	65.611.13	0.75	6
65.611.21	65.611.22	65.611.23	2.5	2
-	65.611.32	65.611.33	5	1

OSCULATI



SP Premium 365 antifouling paint

Self-polishing antifouling paint based on copper oxide free organic biocide. Compatible with any hull (fibreglass, aluminium, wood, etc.). Yield: 8 m²/l, colour 7 m²/l. Recommended for aggressive weather conditions all year round.

Minimum temperature of application 10° C. Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

Restricted to professional users. EU Regulation 2020/1182.

white	blue	Black	Package I	PACKAGE
65.602.11	65.602.12	65.602.13	0.75	6
65.602.21	65.602.22	65.602.23	2.5	2

OSCULATI



HM Premium 365 antifouling paint

Hard matrix antifouling paint based on copper oxide free organic biocide. Compatible with any hull (fibreglass, aluminium, wood, etc.). Yield: 8 m²/l. Recommended for aggressive weather conditions all year round.

Minimum temperature of application 10° C. Covering temperature: 6h at 20° C. Curing time before launching: 12h at 20° C.

Restricted to professional users. EU Regulation 2020/1182.

white	blue	Black	Package I	PACKAGE
65.612.11	65.612.12	65.612.13	0.75	6
65.612.21	65.612.22	65.612.23	2.5	2

OSCULATI

