





## "Turbo Max" Electric inflator pump for dinghies

It inflates and deflates and automatically stops at set pressure. Built-in LED troubleshooting.

| Code      | Functions                | ٧  | w       | Flow<br>I/min | Max<br>pressure       | Current<br>draw A | ←→  <sub>mm</sub> | Tube               |
|-----------|--------------------------|----|---------|---------------|-----------------------|-------------------|-------------------|--------------------|
|           | Inflation+defla-<br>tion |    | 540/720 | 1000          | 250 mbar (3.6<br>PSI) | 45/60             | 310x180x190       | 66.447.02 Optional |
| 66.448.00 | Inflation+defla-<br>tion | 24 | 700/800 | 1000          | 250 mbar (3.6<br>PSI) | 23/26             | 310x180x190       | - Included         |



66.447.02 25-mm@tube, 25-m roll, OPTIONAL.



## BRAVO Turbo Max Kit electric inflator for dinghies

#### Fixed version, for recess mounting.

Ideal for installation on the console of the dinghy or near the tender garage.

Inflator/deflator. Automatic stop at the set pressure.

| Code      | Functions                | ٧         | w       | Flow I/min | Current<br>draw A | ←→  <sub>mm</sub> | OPTIONAL watertight case | OPTIONAL<br>hose |
|-----------|--------------------------|-----------|---------|------------|-------------------|-------------------|--------------------------|------------------|
| 66.447.01 | Inflation+de-<br>flation | 12 540/72 |         | 1000       | 45/60             | 330x210x230       | 66.447.03                | 66.447.02        |
| 66.448.01 | Inflation+de-<br>flation | 24        | 525/930 | 1000       | 25/30             | 330x210x230       | 66.447.03                | 66.447.02        |



66.447.02 25-mm@tube. 25-m roll. OPTIONAL.

66.447.03 Watertight case with clear lid for mounting flush with the steering console. Dimensions: 345x220x18 mm. Depth: 130 mm. OPTIONAL.



## High-pressure electric inflater with GE 22 RC remote-controlled compressor

It consists of a pumping unit to be located in a protected housing and a control panel that can be positioned in a different place depending on your boat (tender garage, stern gangplank, boat deck). The 5-m long hose and cables connecting the pump to the panel are included.

The function (inflation/deflation) and the pressure needed can be selected on the control panel, where the inflating mouth is located.


Connect one end of the inflation hose to the control panel and the other end to the dinghy and press ON to start the pump.

The remote-controlled pump drastically reduces noise during operation.

High-performance pump for fast and high-pressure inflation.

For dinghies, ribs, SUPs, etc.

| Code          | Functions                | v  | Current | Flow/                         | pressure                               | ←→                 | ←→               |
|---------------|--------------------------|----|---------|-------------------------------|--|--------------------|------------------|
| oode          | Tunctions                | •  | draw A  | Motor 1                       | Motor 2                                | Pump<br>mm         | panel<br>mm      |
| 66.447.05     | Inflation+<br>deflation  | 12 | 30      | 250 l/min<br>up to 0.2<br>bar | 120 l/min up<br>to 1.4 bar<br>(20 PSI) | 370 x 170<br>x 152 | 151 x 90 x<br>51 |
| 66.447.06 New | Inflation +<br>deflation | 24 | 15      | 250 l/min<br>up to 0.2<br>bar | 120 l/min up<br>to 1.4 bar<br>(20 PSI) | 370 x 170<br>x 152 | 151 x 90 x<br>51 |









# New

# Electric Inflator SCOPREGA Maxxive Infinite wall mounting

4-m hose

w/connections

OPTIONAL

66.447.07

66.447.07

MAXXIVE INFINITE inflator stands out for high performances (1.2 bar and 500 l/min of initial volume) and ability to inflate and deflate a wide range of objects, including kites, SUPs, small inflatable boats, air mattresses, etc...

 $Integrated \ touch screen \ for intuitive \ control\ and\ very\ low\ noise\ level.\ User-friendly, fast\ and\ quiet.$ 

|  | Code      | F                        | v  | Current | Flow/                        | oressure                            | 14                | Weight |
|--|-----------|--------------------------|----|---------|------------------------------|-------------------------------------|-------------------|--------|
|  | Code      | Functions                | v  | draw A  | Motor 1                      | Motor 2                             | ←→  <sub>mm</sub> |        |
|  | 66.450.12 | Inflation +<br>deflation | 12 | 23      | 500 I/min up to<br>0.150 bar | 150 I/min up to 1.2<br>bar (17 PSI) | 240 x 165 p.175   | 2.15   |
|  | 66.450.24 | Inflation+<br>deflation  | 24 | 12      | 500 l/min up to<br>0.150 bar | 150 I/min up to 1.2<br>bar (17 PSI) | 240 x 165 p.215   | 2.65   |