

LEWMAR HTX aluminium blocks

LEWMAR®

LEWMAR HTX block (50 - 60 - 72 - 90 mm)

A range of high-performance blocks in terms of load capacity and smoothness, which has received numerous awards during its presentation. The aluminum cheeks ensure optimal load distribution between the sheave and the attachment, guiding the line perfectly when the load is not aligned and also when the line works at incorrect angles. Compared to products on the market, they have a significantly higher load resistance for the same diameter. The sheave runs on a bushing and Torlon balls.

Type	50 Ø sheave			60 Ø sheave			72 Ø sheave			90 Ø sheave		
	Code	maximum working load	for maximum ropes	Code	maximum working load	for maximum ropes	Code	maximum working load	for maximum ropes	Code	maximum working load	for maximum ropes
Single with stand-up	68.600.50	800	10	68.600.60	800	10	68.600.72	800	10	68.600.90	800	10
Single	68.601.50	3500	16	68.601.60	3500	16	68.601.72	3500	16	68.601.90	3500	16
Double	68.602.50	800	10	68.602.60	800	10	68.602.72	800	10	-	800	10
Triple	68.603.50	1100	12	68.603.60	1100	12	-	1100	12	-	1100	12
Single with groove	68.604.50	800	10	68.604.60	800	10	68.604.72	800	10	68.604.90	800	10
double with rope guide	68.605.50	1100	12	68.605.60	1100	12	-	1100	12	-	1100	12
Single with fork head	68.621.50	800	10	68.621.60	800	10	68.621.72	800	10	-	800	10
Single with cleat and throttle	68.609.50	800	10	-	800	10	-	800	10	-	800	10
Triple with cleat and stopper	68.610.50	800	10	68.610.60	800	10	-	800	10	-	800	10
Fiddle	68.631.50	1100	10	68.631.60	1100	10	68.631.72	1100	10	-	1100	10
Fiddle with becket and cam	68.639.50	2000	12	68.639.60	2000	12	68.639.72	2000	12	-	2000	12



▲ 68.601.xx Single



▲ 68.602.xx Double



▲ 68.603.xx Triple



▲ 68.604.xx Single with surcharge



▲ 68.605.xx Double with intake



▲ 68.609.xx Single with haulage and throttle



▲ 68.610.xx Triple with retrieval and choke



▲ 68.621.xx Single with fork head



▲ 68.631.xx Violin



▲ 68.639.xx Violin block with cleat and ratchet



▲ 68.600.xx Single with stand-up

LEWMAR snatch blocks

LEWMAR®

LEWMAR snatch block

Opening snatch blocks with soft, synthetic rubber cheeks to protect the deck and Synchro quick-release snap shackle. Ideal for general spinnaker use and to resist rough treatment.



Code	Max working load kg	max Ø tip mm	Pulley	
			Ø mm	material
68.906.01	1135	14	66	Delrin
68.906.02	1590	16	80	Delrin
68.906.03	2155	16	80	Aluminium
68.906.05	4000	22	125	Aluminium