

TOP SNAPPER tool

Device to open automatic pins without ripping off the fabric.

Code	Material
10.299.75	SS and nylon

**Pliers for snap fasteners 10.301.XX / 10.303.XX**

Code	Description
10.299.85	Supplied without punches.

Deck press for snap fasteners 10.301.XX / 10.303.XX

Code	Description
10.299.80	Supplied without punches.

Punch set for snap fasteners 10.301.XX / 10.303.XX

Code	Match to	
	press	pliers
10.299.90	10.299.80	10.299.85

CAF-COMPO universal composite screw studs

It is compatible with all buttons on the market.

Available in various colors to perfectly match the installation point.

The screw is already integrated, allowing for greater speed in installation.

Versions:

A: suitable for all materials, including fiberglass, wood, and other composites.

B: developed for use in sandwich-constructions with min. 10-mm core thickness.

C: Metric thread for screwing into aluminium or iron (profiles, hulls, windscreens, etc.).

CAF-COMPO
made to match





Code	Version	Stud	Thread	Colour	 ORDER BY BOX
10.501.11	A	Universal	long	☐ white	100
10.501.41	A	Universal	long	☒ black	100
10.502.10	B	Universal	Short	☐ white	10 (blister)
10.502.11	B	Universal	Short	☐ white	100
10.503.31	C	Universal	Metric	☒ grey	100
10.503.41	C	Universal	Metric	☒ black	100

**STAYPUT Press Clip plastic snap fasteners**

UV-resistant and corrosion-resistant nylon products. They are easy to install and have a guaranteed and durable seal. Required hole size in fabric 5 mm. Ø head mm 18

Cap			Stud			Support		
white	black	 ORDER BY BOX	white	black	 ORDER BY BOX	white	black	 ORDER BY BOX
10.313.01	10.313.51	100	10.313.02	10.313.52	100	10.313.03	10.313.53	100
10.314.01	10.314.51	1000	10.314.02	10.314.52	1000	10.314.03	10.314.53	1000



▲ 10.313.01;
10.314.01



▲ 10.313.03;
10.314.03



▲ 10.313.02;
10.314.02



▲ 10.313.51;
10.314.51



▲ 10.313.52;
10.314.52



▲ 10.313.53;
10.314.53