


OSCULATI




Trefoil® anchor made of hot-galvanized cast steel

With progressive penetration system.

Code	kg	A mm	B mm	C mm
01.110.02	2	175	358	210
01.110.05	5	273	469	310
01.110.07	7.5	298	531	360
01.110.10	10	320	583	375
01.110.13	12.5	330	630	395
01.110.15	15	335	655	425
01.110.20	21	395	701	470
01.110.30	32	410	800	560
01.110.50	50	470	980	660
01.110.80	80	560	1100	720

OSCULATI




Trefoil® anchor made of mirror-polished AISI316 stainless steel

AISI 316

Hand-crafted investment cast steel. Perfect aesthetic and dimensional result.

Code	kg	A mm	B mm	C mm
01.109.25	2.5	170	357	235
01.109.05	5	240	470	320
01.109.07	7.5	270	540	360
01.109.10	11	310	590	385
01.109.15	15	335	645	450
01.109.20	20	355	660	475
01.109.30	30	410	815	560
01.109.50	50	495	1000	665

OSCULATI




Trefoil® stainless steel slide anchor with gripping plate

Slide anchor with lock for low bows (similar to rubber dinghies) and inverted bows.

Code	kg	A mm	B mm	C mm
01.117.10	10	320	570	385

OSCULATI




Trefoil® folding grapnel anchor made of hot-galvanized cast steel

PATENT

The huge holding power of Trefoil® anchors combines with the convenience of folding grapnel anchors that are easily stowed onboard.

Code	kg	A mm	B mm	C mm
01.104.05	5	240	469	315
01.104.07	7.5	273	531	361

LEWMAR



LEWMAR C.Q.R.® anchor

Lifetime warranty against breaks and Lloyd's Test Certification as High Holding Power anchor.

Metal frame	Forged	kg	Recommended chain mm	Recommended for hulls up to m	A mm	B mm	C mm	D mm	E mm
01.147.07	01.145.65	7	6	6	626	253	82	439	287
01.147.09	01.145.09	9	8	9	690	279	86	484	313
01.147.11	01.145.11	11	8	11.5	740	299	90	552	336
01.147.16	-	16	8	14	827	335	94	584	373
01.147.20	-	20	10	18	901	366	100	635	405
01.147.27	01.145.27	27	10	19	989	402	106	700	445
01.147.34	-	34	11	20	1071	435	112	754	481
-	01.145.64	66	12.5	22	1337	537	128	933	583