

Nemo navigation lights up to 20 m, RINA type-tested



Nemo LED navigation lights for vertical mounting



LED

AISI 316

Black polycarbonate body and mirror-polished AISI316 stainless steel case. Easy to install on both the hull and the deck.

RINA type-approved in compliance with the COLREG72 regulations. For vessels up to 20 metres with visibility not exceeding 2NM.

RETAIL	Bulk 6 pairs	Content	Light colour	Visibility NM	V	W
11.470.01	11.470.01BU	Couple of lights	 112.5° left + 112.5° right	2	12	0.4+0.4
11.470.04	11.470.04BU	Single light	 135° stern	2	12	0.4



OSCULATI



11.470.01/01BU



11.470.01/01BU



11.470.04/04BU

Nemo LED navigation lights for recess mounting


LED

AISI 316

Black polycarbonate body and mirror-polished AISI316 stainless steel case. Easy to install on both the hull and the deck.


For optimal orientation of the light sector, it is recommended to mount on a surface angled at about 22° relative to the bow axis.

RINA type-approved in compliance with the COLREG72 regulations. For vessels up to 20 metres with visibility not exceeding 2NM.

RETAIL	Bulk 6 pair	Content	Light colour	Visibility NM	V	W
11.473.01	11.473.01BU	Couple of lights	 112.5° left + 112.5° right	2	12	0.4+0.4



OSCULATI






Nemo LED navigation lights for horizontal mounting


LED

AISI 316

Black polycarbonate body and mirror-polished AISI316 stainless steel case. Easy to install on both the hull and the deck.

RINA type-approved in compliance with the COLREG72 regulations. For vessels up to 20 metres with visibility not exceeding 2NM.

RETAIL	Bulk 6 pairs	Content	Light colour	Visibility NM	V	W
11.480.01	11.480.01BU	Couple of lights	 112.5° left + 112.5° right	2	12	0.4+0.4
11.480.03	11.480.03BU	Single light	 225° bow	3	12	0.4
11.480.05	11.480.05BU	Single light	 112.5° + 112.5° bicolor	2	12	0.4



OSCULATI



11.480.01/01BU



11.480.03/03BU



11.480.05/05BU



11.480.05/05BU