

LED day/night ceiling light, recessless version

IP66

White/red/off touch switch.

Code	Finishing	V	W	Switch	lumen	K	LED beam angle	No of LEDs	Light colour
13.408.11	white + SS profile	12/24	3.5	Yes	251	3000	120°	18 x white / 6 x red	<input type="checkbox"/> White + <input type="checkbox"/> Red
13.408.12	Chromed finish ring	12/24	3.5	Yes	251	3000	120°	18 x white / 6 x red	<input type="checkbox"/> White + <input type="checkbox"/> Red




Extract and Light recess-fit LED spot light with extractor fan

Compact extractor fan with built-in LED light for application in toilets and kitchens.

Extraction and light are independent.

Fitted with **double finish ring** made of **white or chromed ABS**.

Code	V	W LED HD	Fan current draw W	Suction capacity m³/h	K	Light colour
13.582.12	12	1.5	3.7	7.2	6000	<input type="checkbox"/> white
13.582.24	24	1.5	4.8	7.2	6000	<input type="checkbox"/> white



Metal spotlights and ceiling lights

LED ceiling light, wired recessless version

IP67

FLUSH MOUNT

ABS body, stainless steel finish ring.

Code	Finishing	V	W	lu-men	K	LED beam angle	No of LEDs	Light colour
13.179.52	Mirror-polished	12/24	1.2	95	5500/6300	120°	6	<input type="checkbox"/> white
13.179.53	Mirror-polished	12/24	1.2	13	-	120°	6	<input checked="" type="checkbox"/> blue

Sterope halogen ceiling light for recess mounting

IP65

Stainless steel body. Glass lens. Dichroic parabola. Fixing system with internal springs.

Code	Finishing	V	W	Bulb	Spare bulb	Light colour
13.438.01	Mirror-polished	12	10	G4	14.453.01; 14.100.24	<input type="checkbox"/> white

ALTAIR compact and adjustable LED spotlight

IP20

LED

Glass lens. Fixing system with internal springs.

Code	Finishing	V	W	Reflector	Light colour	LED
13.437.15	Mirror-polished	12/24	3	Optical	<input type="checkbox"/> white	1 HD

Recess-fit adjustable LED ceiling light

IP20

Chromed light alloy case, stainless steel parts. Polycarbonate lens. 3030 LED, warm light.

Code	Finishing	V	W	lu-men	K	LED beam angle	No of LEDs	mm	
								recess	Ø external
13.437.20	Chromed	12/24	2	130	3000	120°	1	14.5	92
13.437.21	Chromed	12/24	4	260	3000	120°	1	14.5	115





13.408.12



13.408.11




13.179.52




13.437.20



13.437.21



13.437.20



13.437.21

