

LED light strip

IP66

LED

Light strip made of clear thermoplastic with 2835 LEDs. 4-screw mounting or with double-sided tape. 100% watertight. LEDs are embedded in the front resin element. ideal for indirect lighting in dinettes and cabins.

Code	V	W	lumen	K	LED beam angle	No of LEDs	LED colour	Length mm	Section mm
13.844.01	12	3	265	5800	120°	17	white	229	22x11
13.844.06	12	6	529	5800	120°	45	white	508	22x11
13.844.02	12	3	54	-	120°	17	blue	229	22x11
13.844.07	12	6	153	-	120°	45	blue	506	22x11
13.844.04	12/24	1.2	15/61/18/94	-	120°	15	- RGBW*	225	22x11
13.844.05	12/24	2.4	42/169/46/234	-	120°	39	- RGBW*	508	22x11

* Selectable colors

Ambient strip lights, flexible version

Self-adhesive, waterproof, equipped with a terminal microconnector that allows them to be connected in series and a connection cable with microconnector. LED "Superbright" high brightness.

Code	V	W	Absorption mA	lumen	K	LED beam angle	No of LEDs	LED colour	Length mm	Section mm
13.834.01	12	1.4	70	100	3000	120°	12 SMD	white	300	10x3
13.834.03	12	1.4	70	30	-	120°	12 SMD	blue	300	10x3
13.834.05	12	1.8	90	165	3000	120°	15 SMD	white	500	10x3
13.834.06	12	1.8	90	50	-	120°	15 SMD	blue	500	10x3
13.834.08	12	3.6	150	330	3000	120°	30 SMD	white	1000	10x3
13.834.09	12	3.6	150	100	-	120°	30 SMD	blue	1000	10x3
13.834.11	12	5.4	200	500	3000	120°	45 SMD	white	1500	10x3
13.834.12	12	5.4	200	150	-	120°	45 SMD	blue	1500	10x3

Flexible LED light strip

IP65

Complete with 30 cm bipolar terminal cable.

They can be cut every 2.5 cm (12 V) or every 5 cm (24 V).

Self-adhesive with original 3M tape.

Code	V	W	Lumen / metre	K	LED beam angle	No of LEDs	LED colour	Length mm	mm
13.842.01	12	12	1000	3000	120°	120	Warm white	1000	10x4
13.842.02	12	24	1000	3000	120°	240	Warm white	2000	10x4
13.842.03	24	12	1000	3000	120°	120	Warm white	1000	10x4
13.842.04	24	24	1000	3000	120°	240	Warm white	2000	10x4
13.842.11	12	12	300	-	120°	120	blue	1000	10x4
13.842.12	12	24	300	-	120°	240	blue	2000	10x4
13.842.13	24	12	300	-	120°	120	blue	1000	10x4
13.842.14	24	24	300	-	120°	240	blue	2000	10x4

Neon Light flexible LED strip, even light

IP68

2-m bars. They can be very easily **cut to measure** keeping into account that the master contact is placed every 50 cm (marked on the bar).

Yet the bar can also be cut every **10 or 5 cm** (thus avoiding waste) being extremely careful in the process.

This technology delivers **even and diffused light**.

For interior and exterior applications.

Code	V	W/m	lumen	K	LED beam angle	No of LEDs/m	LED colour	Length m	Section mm
13.701.12	12	10	380	3000	120°	120	Warm white	2	8x16
13.701.24	24	10	380	3000	120°	120	Warm white	2	8x16
13.702.12	12	10	100	-	120°	120	Blue	2	8x16
13.702.24	24	10	100	-	120°	120	Blue	2	8x16



13.710.04 End cap.

13.710.01 Electric cord fitted with 1 junction.

13.710.02 Electric cord to connect 2 bars fitted with 2 junctions.

13.710.03 Aluminium clips for strip mounting

