

OSCULATI**New****Classic electric spotlight with console-operated joystick**

Body: diecast aluminium coated in white high-resistance anti-corrosion resins. Totally watertight. 2-speed 355° horizontal rotation. 50° vertical rotation.

Version A: 100W+90W double filament halogen bulb (spot + flood).

Version B: ultra-powerful HID Xenon gas discharge bulb (35W HID).

Protection against electronic interference.

Headlights can be connected to 2 types of optional controls (independent or combined) for the desired configuration:

1) Console-operated joystick. 4.5-m cable included. Additional joystick controls to be installed via the 2-port cable 13.227.51.

2) Traditional remote control with bracket for console fixing. Range up to 40 m from the lighthouse.



▲ 13.226.50



▲ 13.225.50



▲ 13.225.49; 13.226.49






▲ 13.225.31




▲ 13.227.51

Code	V	CD candles*	W	lumen	Range 0.25 lux*	Joystick control INCLUDED or 2nd control	OPTIONAL wireless remote control	Connection cable for second joystick 4.5m	10-m extension cable for OPTIONAL Joystick	Spare bulb
13.225.01	12	180.000	100+90	2500	849	13.225.49	13.225.50	13.227.51	13.225.31	13.225.35
13.225.02	24	180.000	100+90	2500	849	13.225.49	13.225.50	13.227.51	13.225.31	13.225.36
13.224.01	12	315.000	35	3200	1122	13.226.49	13.226.50	13.227.51	13.225.31	13.224.32
13.224.02	24	315.000	35	3200	1122	13.226.49	13.226.50	13.227.51	13.225.31	13.224.32

* To be measured at the centre of the light beam.



▲ 13.225.49; 13.226.49



▲ 13.225.49; 13.226.49

**OSCULATI****New****Classic electric SS spotlight with console-operated joystick****IP67**

Mirror-polished stainless steel body. 100% watertight. 350° horizontal and 55° vertical rotation. Two speeds. 100W + 90W H4 halogen double-filament bulb (spot + flood).

Protection against electronic interference.

Headlights can be connected to 2 types of optional controls (independent or combined) for the desired configuration:

1) Console-operated joystick. 4.5-m cable included. Additional joystick controls to be installed via the 2-port cable 13.227.51.

2) Traditional remote control with bracket for console fixing. Range up to 40 m from the lighthouse.



▲ 13.225.50



▲ 13.225.49





▲ 13.225.31




▲ 13.227.51

Code	V	CD candles*	W	Range 0.25 lux*	Joystick control INCLUDED or 2nd control	OPTIONAL wireless remote control	Connection cable for second joystick 4.5m	10-m extension cable for OPTIONAL Joystick	Spare bulb
13.229.01	12	135.000	100/90	775	13.225.49	13.225.50	13.227.51	13.225.31	13.225.35
13.229.02	24	135.000	100/90	775	13.225.49	13.225.50	13.227.51	13.225.31	13.225.36

* To be measured at the centre of the light beam.



▲ 13.225.49



▲ 13.225.50

