

Lights for topsides, gangplanks and below the waterline

Pair of LED docking lights



IP65

LED

AISI 316

Mooring lights with 2 options: bow light with 20° angle, HD LED 2.8 W and side light with 85° angle, 1.2 W. Both lights are controllable separately. No recess required. Body in polished AISI 316 stainless steel.

Code	Description	V	LED	K	lumen	LED beam angle	↔ mm
13.653.00	Docking lights	12	320+80 mA	6000	280/125	20° + 85°	90.8x66.2x20






Compact fairing light pair with LED bulb

AISI 316

Manufactured in mirror-polished AISI 316 stainless steel. Front protection lens.

Code	LED included	Spare LED	Cone
13.254.13	12 V 4 W	14.258.56	45° FMW



OSCULATI





Fairing light pair, built-in model fitted with Sealed Beam 4" watertight bulb.

AISI 316

Made of mirror polished AISI 316 stainless steel.

Code	Cone	Bulb included	Spare bulb
13.258.12	70°x30°	12 V - 50 W x 2	14.249.11
13.258.24	40°x5°	24 V - 50 W x 2	14.249.08



OSCULATI



Transom light made by white ABS, 100% watertight

Fitted with Sealed Beam bulb 14.249.07/08. To be mounted under the platform to illuminate the water surface; supplied with 1.20 m power cable.

Code	Version	Type	Base Ø mm	Overhang mm
13.256.12	sloped	12 V - 35 W	170	90
13.256.24	sloped	24 V - 50 W	170	90

OSCULATI

