



OSCULATI**Underwater light with screws for hull / transom / platform****IP68**

Manufactured in mirror-polished AISI 316 stainless steel, equipped with high-power LEDs and a parabolic system to increase brightness.
Can only operate submerged in water.

Code	Version	V	A	K	Lux at 1 m	lu-men	LED beam angle	LED	LED colour	Ø mm
13.294.01	With screws	12/24	1.5	6000	26000	1500	15°	6x3 W	white	114
13.294.02	With screws	12/24	1.5	6000	26000	-	15°	6x3 W	RGBW	114
13.295.01	With screws	12/24	1.5	-	-	400	15°	6x3 W	blue	114
13.298.01	With screws	12/24	3.0	6000	52000	3000	15°	12x3 W	white	140
13.298.02	With screws	12/24	3.0	6000	52000	-	15°	12x3 W	- RGBW	140
13.299.01	With screws	12/24	1.5	-	60000	800	15°	12x3 W	blue	140
13.300.01 New	With screws	12/24	5	6000	60000	7200	25°	18x3 W	white	140
13.300.02 New	With screws	12/24	5	-	-	1350	25°	18x3 W	blue	140



▲ 13.298.01/02;
13.299.01



▲ 13.294.01/02; 13.295.01

**Underwater Led light**

Operates with a single ultra-powerful 10 W LED.

Technical data: protrusion only 5 mm; power supply: 12/24 V; LED no. 1 x 10 W; Ø hull hole 63 mm.

They can be installed both above and below the waterline.

Manufactured from reinforced technopolymer and aluminium fins.



Code	K	lumen	LED beam angle	LED	LED colour	LED life h
13.270.10	6000	900	30°	1x10 W	white	50.000
13.270.11	-	140	30°	1x10 W	blue	50.000
13.270.02	-	-	30°	1x10 W	- RGBW	50.000

