


## Countertop battery switch with removable key

Cable outlet on 4 sides.

Code	Max capacity A 50V DC			Ø pins mm	↔  mm
	for 30 sec.	in continuous	intermittent		
14.923.11	1000	300	500 A	10	69x69x74 h



OSCULATI



## Battery switch, flat-mounting model without recess fitting



Watertight, "CE" type-tested (EN ISO 28846); removable clip-on connecting key.

Code	Max capacity A		Base mm	Overhang mm	Pins mm
	for 5 sec.	in continuous			
14.383.00	2200	250	70x70	75	10



## Heavy Duty marine battery switch with removable key

Fitted with splash-proof key with **nickel-plated brass** pin, sealing cap with back fairing. "CE" type-tested in compliance with Directive 94/25/CE; polycarbonate body and copper contacts. Possibility of built-in bulkhead.

Code	Max capacity A		Flange Ø mm	Front projection mm	Bulkhead thickness mm	Pins mm
	for 5 sec.	in continuous				
14.382.01	2500	290	72	45/60	4/19	10



## Heavy Duty marine battery switch, built-in model

Fitted with removable **nickel-plated brass** key; "CE" type-tested in compliance with directive 94/25/CE. Obligatory for mounting on a positive cable, under ISO 10133 standards.

Code	Max capacity A		Flange Ø mm	Inside overhang, clamps included mm	Colour	Pins mm	Spare key
	for 5 sec.	in continuous					
14.385.50	2500	280	105	99	white	10	14.385.51
14.385.40	2500	280	105	99	Cream RAL 9001	10	14.385.51
14.385.55	2500	280	105	99	Black	10	14.385.51



## Battery switch for semi-recessed mounting

IP68

Made of polycarbonate, mounting on flange. ON-OFF-OUT position that allows to pull out the knob for anti-theft purposes.

Code	Max capacity A 50V DC			Flange mm	Ø pins mm
	for 30 sec.	in continuous	intermittent		
14.385.25	1000	300	500	72x72	10



## Battery switch with remote electric control

This battery switch can be mounted near the battery thus reducing the length and diameter of copper cables. Equipped with emergency manual control and LED indicators for functioning. The remote control is operated by an ON-OFF switch.

Code	V	Max capacity A		↔  mm	OPTIONAL switch
		intermittent	in continuous		
14.386.08	12/24	455	275	67x67x95h	14.386.09

14.386.09 OPTIONAL ON-OFF 12V switch with double key and LED warning light. Dimensions: 69x69x45 mm.

