

Fuse holder boxes

Accept standard blade fuses (ATP - ATO - ATC). Complete with control LED on each fuse. Voltage 12/24 V. Max cumulative load 100 A. Max single fuse load 20 A. Adhesive label kit with various inscriptions included in the package. Using base modules 1 and 2, it is possible to compose the illustrated combinations and others. The only limit is the total max load of the fuse holders of 100 A.

Code	Type	Fuse holders	Contacts	mm
14.182.01	basic module	6-unit fuse holder	Faston	86x78x41
14.182.02	basic module	12-unit negative bus bar	Faston	86x57x41

OSCOLATI


14.182.01+14.182.02



14.182.02



14.182.01



14.182.01+14.182.02




14.182.01+14.182.02




14.182.01 (1)




14.182.02 (2)




1



2+1



1+1



2+1+1

composition examples / esempi di composizione

Circuit breaker holder box

It is compatible with standard circuit breakers (ex. 14.733.xx) that are easier to install than blade fuses.

With clear lid with a space for function labels (60 x labels standard supply).

The watertight circuit cap allows to reset the circuits without removing the lid.

Screw terminals.

Code	V	Power supply	Maximum per circuit	To cumulative maximums	mm
14.182.06	max 32	Independent	30	100	40
14.182.07	max 32	Common	30	100	40

Independent supply version: the user can configure at the same time permanent circuits (automatic bilge pumps, alarms, etc.) or ON-OFF circuits (lights, stereo, refrigerator, etc.)




Watertight blade fuse holder box

It can be used with standard, mini and micro fuses. Clear lid and watertight seal. Bayonet terminals.

Code	Fuse holders	Base mm	Max capacity A	Max capacity single fuse
14.100.31	4	85x31	30	15
14.100.32	6	100x31	45	15
14.100.33	8	120x31	60	15
14.100.34	10	140x31	90	15



14.100.31



14.100.31

Watertight blade fuse holder with deep lid

It can be used with the following fuses: **standard, mini, micro, standard resettable, mini resettable et micro resettable.**

Code	Fuse holders	Base mm	Max load A	Maximum single fuse load
14.100.81	4	85x31	30	15
14.100.82	6	100x31	45	15
14.100.83	8	120x31	60	15
14.100.84	10	140x31	90	15



14.100.81



14.100.81