




▲ 15.290.12




▲ 15.290.13/15/11/10



▲ 15.290.14 Angled



▲ 15.290.11/13



▲ 15.290.11/13 Straight



▲ 15.290.14



▲ 15.290.10/15

### WHALE Twist integrated deck shower

#### PATENT/BREVETTATO

The hot/cold water temperature and the flow rate are set in an easy and user-friendly way by rotating the lower part of the shower head body. Its flow (8 lt/min) ensures a powerful water jet.


ABS body and grey rubber edges (blue rubber on request) to protect the deck from unwanted impacts.

Easy installation:

- Special section pipe with T-joint and pre-installed quick-release couplings;
- The flange can be installed from the outside with just one circular bore.

| Code      | Function   | Flange           | Colour | Min. inner space mm | Flange Ø mm | tube cm | Package    |
|-----------|------------|------------------|--------|---------------------|-------------|---------|------------|
| 15.290.14 | Hot/ cold  | Angled           | grey   | 150                 | 120         | 250     | bulk/loose |
| 15.290.12 | Cold, only | Angled           | Black  | 150                 | 120         | 250     | bulk/loose |
| 15.290.13 | Hot/ cold  | straight         | grey   | 190                 | 57          | 250     | bulk/loose |
| 15.290.15 | Hot/ cold  | Straight/ Angled | grey   | 190/150             | 57/120      | 250     | retail box |
| 15.290.11 | Cold, only | straight         | grey   | 190                 | 57          | 210     | bulk/loose |
| 15.290.10 | Cold, only | Straight/ Angled | grey   | 190/150             | 57/120      | 210     | retail box |


The angled version is suitable for installation on vertical walls and where there is limited inside space.



### WHALE shower hose bag

**Code** 15.290.50

Convenient plastic-mesh bag made for the hose of the below-deck shower to prevent getting entangled in the other equipment and making it impossible to extract the shower head. Easy to fasten and adapt to all situations, resistant and inexpensive.



### WHALE recess-fit deck shower

Removable 2.10-m hose connected to the deck shower. 1/2" thread white ABS hose adaptor for connection.

| Type     | With lid  | Without lid | Replacement shower head only |
|----------|-----------|-------------|------------------------------|
| Hot/cold | 17.030.06 | 17.031.06   | 17.030.99                    |



### Deck shower with Mizar push-button shower head and mixer

Chromed brass shower head, UV-resistant ASA housing. Fitted with hot/cold water mixer. Model designed to be mounted preferably on the bulkhead, hose exit parallel to the bulkhead.

| Code      | mm     |                       |                  | Pipe in | Hose m | Replacement mixer | Spare shower head |
|-----------|--------|-----------------------|------------------|---------|--------|-------------------|-------------------|
|           | recess | depth                 | outer dimensions |         |        |                   |                   |
| 15.239.01 | 195x95 | 47 (box) + 87 (mixer) | 240x145          | Net PVC | 2.5    | 17.051.01         | 15.242.02         |
| 15.239.02 | 195x95 | 47 (box) + 87 (mixer) | 240x145          | Net PVC | 4      | 17.051.01         | 15.242.02         |