

WHALE hand pumps



WHALE plastic bilge pump

Top quality pump fitted with drain spiral pipe and terminal outlet. Suitable for gasoil pouring. Sold in display package.

Code	Capacity l/m	Body length mm
15.264.35	19/32	380
15.264.55	19/32	580




Manual pump WHALE "Smart Bail"

Fitted with built-in handle; easy to install with just two fastening screws; equipped with built-in gasket thus it does not require the use of silicone; very compact, may be installed in all positions; removable swivelling rear clip-on hose-adaptor; made in accordance with ISO 15083 standards.

Code	Suction	Head	Maximum head	45 cycles / min	60 cycles / min	Hose adaptor mm
15.360.25	0 m 1 m	0 m 1 m	3 m	38.50 l/min 32.75 l/min	51.33 l/min 43.60 l/min	25
15.360.38	0 m 1 m	0 m 1 m	3 m	43.50 l/min 43.50 l/min	58 l/min 58 l/min	38



▲ 15.350.02



▲ 15.350.00

WHALE "Compact 50" pump

Designed for concealed installation, ideal for mounting in confined spaces, fitted with swivelling inlet and outlet jointly with a lower casing. **Also suitable for transferring diesel fuel.** Made of **polypropylene**, fiberglass and nylon 66 reinforcements. Includes handle and clip-in trap door.

Code	Colour	Fixing with	Depth mm	Body mm	Capacity l/m	Hose adaptor mm	Repair kit
15.350.00	white	4 screws	127	199x196	40	25	15.350.01
15.350.02	Black	4 screws	127	199x196	40	25	15.350.01



15.350.99 Closing ring and screws.

15.350.98 Deck sealing kit and screws.

15.350.01 Maintenance kit: diaphragm, valves and screws.



▲ 15.262.35

▲ 15.262.34



▲ 15.262.36

WHALE hand bilge pump


Obligatory on all boats in category A and B, in accordance with current EC standards. High quality product, made with the best materials on the market.

Code	Version	Type of handle	Max flow rate l/m	Hose adaptor mm	URCHIN pump repair kit
15.262.35	GUSHER URCHIN	Fixed	37	25/38	15.262.37
15.262.36	MKIII GUSHER URCHIN *	Removable + Trapdoor	37	25/38	15.262.37
15.262.34	GUSHER URCHIN	removable	37	25/38	15.262.37


*Includes adaptor for concealed installation.




▲ 15.262.37



▲ 15.262.34



▲ 15.262.35




▲ 15.262.36

WHALE MKV pulsatile pump

Fitted with **stainless steel removable** handle, neoprene diaphragm, immediate inspection from the inside through the snap-on cover; can suction any type of liquid, including diesel fuel.

Code	Max. flow rate l/m	Hose adaptor mm	Mounting	Repair kit	Only watertight skylight	kg
15.268.01	75	38	Floor, wall or behind the bulkhead	15.268.04	15.268.05	1.1
15.268.03	75	38	Specific for mounting behind the bulkhead (with watertight trap door) 15.268.05	15.268.04	15.268.05	1.1



▲ 15.268.04



▲ 15.268.05



▲ 15.268.03