Maxi pump WHALE

Made up of two combined MKV pumps; removable handle; concealed installation behind the bulkhead, fitted with trapdoor (to be ordered separately). The entry joints may be removed in order to have two separate pumps and suction from two different bilges, even if one is dry.

Code	Capacity I/m	Hose adaptor mm	Head m	←→ _{mm} excluding handle	Botolina	Repair kit
15.270.00	136 (with 70 turns)	38	4.5	234(h) x 292(w) x 203(d)	15.268.05	15.268.04







Hand pumps

Small double-acting pump



Suitable for extracting oil from the motor sump, or petrol, water, etc.

Code	Capacity cc/pumping	Length mm	
15.260.00	80	230	

Bilge pumps for suction/pressing



Provide easy control of the suctioned liquid, supplied with terminal extension and special discharge **spiral** hose.

Code	Body length mm	Ømm
15.263.35	390	50
15.263.55	550	50

Bilge pumps for suction/pressing



Equipped with 95-cm drain tube. Ergonomic grip handle.

Code	Body length mm	Ømm	
15.265.01	390	44	
15.265.02	550	44	
15.265.03	1000	44	

Double acting hand pump, designed to suction oil



Fitted with nylon hose for fitting onto oil sidepiece and drainage pipe; also suitable for draining needy bilges

Code	Length mm		
15.259.01	390		

Manual double-acting bilge pump



Fitted with central SOFT sleeve for better intake. Drain hose cm 100.

Code Body length mm	Ømm
15.263.00 440	44

Bulkhead hand pump, fixed lever

For surface mounting. Compact and sturdy, made from anti-corrosion materials.

Code	Flow rate I / pumped	Lever	Dimensions mm	Hose adaptor mm	Spare seal kit
15.262.20	0,33 (30 - 60 pumps / minute)	Fixed	180x125x75	25	15.262.21

