

### Europump 4-diaphragm self-priming fresh water pump



It can run dry without damage, no vibrations, very quiet.  
Fitted with internal bypass for inlet pressure control.  
The 4-diaphragm system prevents the pulsations that usually occur in the other fresh water pumps with a semi-open tap.  
**4 plug-in fittings** (2 x 1/2" threads + 1 x 14-mm straight hose adaptor + 1 x 14-mm 90° hose adaptor) and **plug-in inlet strainer**,



Code	Type	V	Flow l/min	Current draw A	Operating pressure of the bar	↔  mm	Spare parts		
							pressure switch	Filter	
16.512.12	Europump 12	12	12.5	4	2.45	213x105x95	16.540.01	16.533.01	2.2
16.512.24	Europump12	24	12.5	2	2.45	213x105x95	16.540.01	16.533.01	2.2
16.518.12	Europump 18HF	12	20	9	2.8	257x105x95	16.540.05	16.533.01	2.7
16.518.24	Europump 18HF	24	20	4.5	2.8	257x105x95	16.540.05	16.533.01	2.7

### EUROPUMP combined fresh water pump and accumulator tank



The system includes a 4-diaphragm fresh water pump fitted with a 1-litre stainless steel accumulator tank and an inlet strainer. Base made of robust ABS 280 x 260 mm. Fixing by means of 4 vibration-damping rubber pads. Inlet connections 1/2" or hose connection 14 mm. 1/2" female outlet.



Code	V	Current draw A	Flow l/min	↔  mm	Installed autoclaves	Stainless Steel Tank	
16.506.03	12	4	12	280x265x140	EUROPUMP 16.512.12	16.126.01	3.4

### Europump Washdown Kit for deck washing



Autoclave 16.518.12/24 complete with filter, featuring a spray jet gun art. 36.189.00 + 36.189.01 + 36.189.02. Ideal for washing decks, bilges, anchors, assemblies, sterns, and propellers. **Complete with 4 fittings** (2 threaded 1/2" + 1 straight hose connector 14 mm + 1 90° hose connector 14 mm) and a **suction filter**, all with a **snap** fitting.



Code	V	Flow l/min	Current draw A	Spare parts	
				pressure switch	Filter
16.520.12	12	20	9	16.540.02	16.533.01
16.520.24	24	20	4.5	16.540.02	16.533.01



### Washdown kit

It includes:  
- 1 x high-pressure 4.2-bar 5-diaphragm fresh water pump.  
- 1 x strainer.  
- 1 x trigger nozzle.  
- 2 x 12-mm hose adaptors.  
- 1 x 7.5-m self-coiling hose.  
It also works with salt water.



Code	V	Flow l/min	Current draw A	Pressure bar
16.521.12	12	21.18	17	4.8
16.521.24	24	21.18	10	4.8