

WHALE Pressure Pump

WHALE Watermaster fresh water pump

IP65

An evolution of the Universal model, the Watermaster 4-diaphragm pump with automatic pressure switch is even quieter and gives high flow rates for systems up to 4 taps. IP65 rated fully sealed protective motor housing. Self-priming up to 3 metres, it works well in dry mode or in salt water. Fitted with a third wire to be connected to a warning light indicating operation. Inlet strainer.

Code		V	Flow l/min	Current draw A	Pressure bar	Input/Output Connection	kg
RETAIL (1pcs)	BULK (10pcs)						
-	16.700.12	12	8	4	2	quick fitting for 15-mm hose	-
16.700.15	16.700.13	12	11.5	8	3	quick fitting for 15-mm hose	1.9




▲ 17.815.87



▲ 16.700.15





▲ 16.700.19



Whale Universal fresh water pump

Very quiet pump. Three models available for 2, 4 and 6 outlets or showers (8, 12 or 18 l / min flow), smooth constant flow, it can run dry without damage, extra protection and safety with wires and pressure switch housed internally, self-priming up to 3 metres, swivelling feet adapt to any existing installation bores. All models include quick fitting strainer. Suitable for use with salt water.

Code	V	Flow l/min	Current draw A	Pressure bar	Entrance	Output	kg
16.700.01	12	8	5	3	15-mm quick fitting	15-mm quick fitting	2.4
16.700.02	12	12	8	3	15-mm quick fitting	15-mm quick fitting	2.4
16.700.04	12	18	12	3	15-mm quick fitting	3/4" male thread	2.9
16.700.05	24	18	8	3	15-mm quick fitting	3/4" male thread	3



18 lit/min
12 lit/min
8 lit/min
universal



▲ 17.815.40



▲ 17.815.87



16.700.19 Inlet strainer

17.815.87 Fitting for BSP 1/2" male threaded outlet.

17.815.40 Joint for 3/4" female threaded outlet.



Easy installation - suitable for 15mm quick connect plumbing direct connection (Whale, John Guest and similar)

WHALE combined fresh water pump and accumulator tank

The system includes one 4-diaphragm fresh water pump fitted with a 1-litre stainless steel accumulator tank and inlet strainer. 280x260-mm base made of sturdy ABS. Mounting by means of 4 vibration-damping grommets, 15-mm inlet and outlet **quick fittings**.

Code	V	Flow l/min	Autoclave installed	Stainless steel tank	kg
16.506.01	12	12	WHALE 16.700.02	16.126.01	4.1
16.506.02	24	18	WHALE 16.700.05	16.126.01	4.4

