




Whale Water System quiet automatic fresh water pump

8-litre accumulator tank.

Code	V	Flow l / min	Current draw A	Quick connection input/output	Pressure bar	Head in m	Maximum suction m	↔ mm	kg
16.701.12	12	12	8	15	3	20	3	200x300x350	6
16.701.24	24	18	8	15	3	30	3	200x300x350	6.9



WHALE high-flow rate fresh water pump

- Two pumps and an accumulator tank ensure a constant water flow rate up to 8 outlets.
- The efficient control systems activates one or two pumps depending on the flow rate required.
- The accumulator tank reduced noisiness and vibration by avoiding the pumps to repeatedly switch on and off.
- The industrial-type external pressure switches have sparkle protection and relays are not needed.
- Retrofitting or installation on new equipment
- Pre-assembled kit for quick installation includes: 2 integrated pumps, 2 external pressure switches, 2 strainers, 1 accumulator tank, mounting brackets and fittings.
- Mounting brackets with vibration-damping feet for reduced dimensions at the base.

Code	V	Flow l/min	Storage can	Quick connection input/output	Maximum Consumption A	Pressure bar	Outlets	Maximum suction m	kg
16.702.12	12	24	2 litres	19	10	3	up to 6	3	10.1
16.703.24	24	32	2 litres	19	8	3	up to 8	3	11



Whale washdown pump

3-bar (45 PSI) high flow pump 16.700.04; 16.700.05 (18 l / min) + trigger nozzle with plug-in fitting 36.189.00; 36.189.01; 36.189.02.

Code	V	Pressure bar
16.700.06	12	3
16.700.07	24	3