

JABSCO - FLOJET fresh water pumps


FLOJET

FLOJET self-priming fresh water pump fitted with 3 valves

3-diaphragm version, it can run dry without damage. Quiet operation, **pulsation-dampening** bypass.

4 fittings (2 x 1/2" threads and 2 x 14-mm with 1/2" hose adapters) and inlet strainer.

Code	V	Flow l/min	Current draw A	Maximum Pressure Bar	↔ mm	kg
16.206.12	12	2.5/7.5	1.9	1.5	101x101x152	2
16.207.12	12	2.5/11	2.9	1.5	127x127x152	2



FLOJET self-priming fresh water pump fitted with 4 valves

It can run dry without damage. **4-diaphragm** inlet system to prevent vibrations. Special internal bypass that protects the pump against incoming overpressure when the pump is connected to the ground water supply network. Permanent magnet motor fitted with shaft bearing.



Code	V	Flow l/min	Current draw A	Self-draining up to m	Fittings	↔ mm	kg
16.440.50	12	From 3,8 to 14,7	2.8	1.80	1/2" threaded bayonet fittings	97x156x207	2.1

JABSCO Washdown Par-Max 6 Plus pump kit

Ideal for washing down, this kit includes a Par-Max HD6 pump (increased pressure 4.8 bar), a 90°-strainer and a trigger nozzle.

Code	V	Flow l/min	Maximum Consumption A	Maximum Pressure Bar	Fuse A	Fittings	↔ mm
16.437.01	12	23	20	4.8	25	2 x 3/4" hose adapters + GHT 3/4" adapter	259x119x129
16.437.02	24	23	10	4.8	15	2 x 3/4" hose adapters + GHT 3/4" adapter	259x119x129



JABSCO Par-Max HD fresh water pump

Constant flow, very silent, self-priming up to 3 m, sealed manostat tested for up to 4 million cycles. The pump can run dry without getting damaged. IPX6 watertight in compliance with ISO 8846 standards.

Fitted with 1/2" snap fittings.

Code	V	Flow l/min	Maximum Consumption A	Maximum Pressure Bar	Fuse A	↔ mm	kg
16.436.01	12	15	10	2.8	15	259x119x129	3.5
16.436.02	24	15	5	2.8	10	259x119x129	3.5
16.436.03	12	23	15	2.8	25	259x119x129	4
16.436.04	24	23	7	2.8	15	259x119x129	4



Pressure switch for FLOJET fresh water pumps (switch assembly)

Code	For pumps
16.901.04	16.440.50
16.901.18	-
16.901.21	16.207.12

Spare fittings for FLOJET pumps



Code	Dimensions	Type	ORDER BY BOX
16.204.06	1/2"	hose adaptor for clamp mounting	2
16.204.07	1/2"	thread	2

Flojet washable water strainers

Version A: plug-in right-angle fittings for the Flojet pump inlet. 40-mesh strainer for **fresh water** and general purposes.

Version B: in-line fittings and fastening support. **Universal** size for any pump or fresh water pump.

Code	Version	Fittings	↔ mm
16.408.02	A	plug-in fitting + 19mm hose adaptor	70x57
16.408.03	A	plug-in fitting + 1/2" thread adaptor	70x57
16.408.05	B	2 from 12 mm	70x57
16.408.06	B	2 x 19mm fittings	70x57

