



Europump Next Generation submersible bilge pump

CE-certified in compliance with the **ISO 8846/8849** directive.
Extremely compact in size, fitted with backflow **check valve**.
Removable hose connector adjustable at 360°.



Code	V	Model	Max flow rate l/min	Current draw A	Head m	Hose adaptor Ø mm	90° Hose holder Ø 29 mm OPTIONAL
16.128.01	12	600	38	2.5	2.5	19/29	16.128.00
16.128.05	12	1100	70	4.0	4	25/29	16.128.00
16.128.06	24	1100	70	2.5	4	25/29	16.128.00
16.128.07 New	12	1500	96	4.5	5	29	16.128.00
16.128.08 New	24	1500	96	2.5	5	29	16.128.00
16.128.09 New	12	2000	128	7.5	5.5	29	16.128.00
16.128.10 New	24	2000	128	4	5.5	29	16.128.00



▲ 16.128.07/08/09/10



▲ 16.128.01/05/06



OSCULATI



▲ 16.128.07/08/09/10



▲ 16.128.01/05/06





▲ 16.128.01/05/06

Europump II automatic bilge pump

Extremely compact, with built-in electronic level sensor. ABS casing, stainless steel shaft.
Reduced power consumption. Removable from base with a snap. CE certification issued by RINA, European Directive 2013/53/EU according to standard **ISO 8846**.


Code	Type	V	Max flow rate l/min	Current draw A	Head m	Hose holder (Ø A) mm
16.124.01	G600	12	38	2.5	2.5	19
16.124.03	G750	12	48	3	3	19
16.124.04	G750-24	24	48	1.6	3	19
16.124.05	G1100	12	70	4.0	3.2	29
16.124.06	G1100-24	24	70	2.0	3.2	29






Europump Next Generation automatic submersible bilge pump

CE-certified in compliance with the **ISO 8846/8849** directive.
Compact in size, fitted with an electronic timer sensing automatic system to check the presence of water every 2.5 minutes for a duration of 0.5 seconds.
Removable hose connector adjustable at 360°.
Fitted with backflow **check valve**.

Code	V	Model	Max flow rate l/min	Current draw A	Head m	Hose adaptor Ø mm	90° Hose holder Ø 29 mm OPTIONAL
16.129.01	12	600	38	2.5	2.5	19/29	16.128.00
16.129.03	12	750	51	3.5	3.0	19/29	16.128.00
16.129.04	24	750	51	2.0	2.0	19/29	16.128.00
16.129.05	12	1100	70	4.0	4.0	25/29	16.128.00
16.129.06	24	1100	70	2.5	2.5	25/29	16.128.00
16.129.07 New	12	1500	96	4.5	5	29	16.128.00
16.129.08 New	24	1500	96	2.5	5	29	16.128.00
16.129.09 New	12	2000	128	7.5	5.5	29	16.128.00
16.129.10 New	24	2000	128	4	5.5	29	16.128.00



▲ 16.129.07/08/09/10



▲ 16.129.01/03/04/05/06

OSCULATI



▲ 16.129.07/08/09/10



▲ 16.129.01/03/04/05/06



▲ 16.129.01/03/04/05/06