

Impellers for inboard engine pumps

ACCESSORIES:


G: gasket; GT: gasket + plug; GX: gasket + grain;

X: grain; CGT: key + gasket + cap;

N: oil-resistant nitrile rubber; T: cap.




▲ G - Gasket



▲ O - O-ring



▲ X - Grain




▲ C - Key



▲ T - Cap



JABSCO inboard pumps



Code Impeller CEF	Impeller OSCULATI	Accessories	Original reference	Ref. CEF	Picture	Insert	Ø A (internal/ external) mm	Ø A mm	Ø B mm	C mm	Blades	Profile no.
16.194.00	16.185.00 New	-	7273-0001; 6303-001	110			7.31 / 8	-	50.8	22.1	6	7
16.194.16	16.185.16 New	-	21414-0001; 21411-0001; 1411-0001 1414-0001	113			8	-	31.3	11.9	6	1
16.194.22	-	-	14787-0001; 14609-0001; 1414-0001	130			8	-	31.75	12	6	3
16.194.29	-	T: cap	17954-0001	109			16.85 / 19	-	66.5	50.6	8	20
16.194.32	-	N: nitrile rubber oil-resistant	1414-0003	230			8	-	31.75	12	6	1
16.194.38	16.185.38 New	-	6303-0001	138			7.31 / 8	-	51.3	22	6	8
16.193.73	16.186.73 New	N: nitrile rubber oil-resistant	6303-0003	238			7.31 / 8.07	-	51.3	22	6	8
16.193.98	-	-	9200-0001	106GT			8	-	40	19	6	6
16.194.01	16.185.01 New	GX: Seal + grain	4528-0001	100			9.5	-	39.6	18.94	6	4
16.194.02	16.185.02 New	GX: Seal + grain	22405-0001; 21951344	121			12	12	39.6	19.2	6	4
16.194.03	16.185.03 New	GX: Seal + grain	653-0001	101			12.17	12.17	50.8	22.1	6	7
16.194.04	16.185.04 New	GX: Seal + grain	673-0001 (6 blades); 21951344; 22222936	116			12.66	-	50.8	22.1	6	7
16.194.31	-	GX: gasket + grain; N: oil-resistant nitrile rubber	4528-0003	200			9.5	-	39.6	18.94	6	4

Accessories: G: gasket; GT: gasket + cap; GX: gasket + grain; X: grain; CGT: key + gasket + cap; N: oil-resistant nitrile rubber; T: cap; HD.K.