


SHERWOOD inboard pumps



Code		Accessories	Original reference	Ref. CEF	Picture	Insert	Ø A (internal/external) mm	Ø A mm	Ø B mm	C mm	Blades	Profile no.
Impeller CEF	Impeller OSCULATI											
16.194.01	16.185.01 New	GX: Seal + grain	9979	100			9.5	-	39.6	18.94	6	4
16.194.10	-	T: cap	10187; 12338	102			15.9 / 16	-	65	50.2	8	11
16.194.14	16.185.14 New	GT: gasket + cap	10615K	120			15.9	15.9	65.2	41.3	12	21
16.194.17	-	GT: gasket + cap	9959K	103			15.9	15.9	62	31.7	12	22
16.194.31	-	GX: gasket + grain; N: Oil-resistant nitrile rubber	9979	200			9.5	-	39.6	18.94	6	4
16.194.36	-	T: cap	18200	214			14.29 / 16	-	65	50.1	10	20
16.194.42	-	G: gasket	15000K	167			16	-	65	51.2	12	20
16.194.48	16.185.48 New	G: gasket	9000K	165			15.95	-	62.2	22.4	12	22
16.194.49	-	G: gasket	10077K	166			12.8	12.8	56.6	19.8	12	26
16.194.63	-	G: gasket	27000K	181			16.1	-	84	73	12	24
16.194.64	-	GX: Seal + grain	18000K	182			20.7	-	94.5	101.5	12	15
16.194.55	16.185.55 New	G: gasket	8000K	190			12.2	12.2	19	40	6	4
16.194.75	-	GX: Seal + grain	29000K	192			20	-	94.5	101.5	12	15
16.194.26	16.185.26 New	T: cap	18200	114			14.29 / 16	-	65	50.1	10	20
16.194.15	-	GT: gasket + cap	17000K	164			20.1	-	84	73.5	12	24
16.194.61	-	GX: Seal + grain	22000K	179			20.7	-	114.3	109.5	10	18

Accessories: G: gasket; GT: gasket + cap; GX: gasket + nut; N: oil resistant nitrile rubber; X: nut; CGT: key + gasket + cap; T: cap.