


VETUS inboard engines



Code		Accessories	Original reference	Ref. CEF	Picture	Insert	Ø A (internal/external) mm	Ø A mm	Ø B mm	C mm	Blades	Profile no.
Impeller CEF	Impeller OSCULATI											
16.194.01	16.185.01 New	GX: Seal + grain	501	100			9.5	-	39.6	18.94	6	4
16.194.02	16.185.02 New	GX: Seal + grain	601	121			12	12	39.6	19.2	6	4
16.194.03	16.185.03 New	GX: Seal + grain	801	101			12.17	12.17	50.8	22.1	6	7
16.194.04	16.185.04 New	GX: Seal + grain	101	116			12.66	-	50.8	22.1	6	7
16.194.31	-	GX: gasket + grain; N: oil-resistant nitrile rubber	501	200			9.5	-	39.6	18.94	6	4
16.194.43	16.185.43 New	X: Grain	701	146			12.17	-	51.8	22	10	9
16.194.05	16.185.05 New	GT: gasket + cap	201	107			14.29 / 16	14.29 / 16	57	31.6	12	26
16.194.34	-	GT: seal + cap; N: oil-resistant nitrile rubber	901	205			22.5 / 25.4	-	96	63.1	9	13
16.194.36	-	T: cap; N: oil-resistant nitrile rubber	301	214			14.29 / 16	-	65	50.1	10	20
16.194.13	16.185.13 New	-	101	129			12.75	12.75	50.8	22.1	6	7
16.193.73	16.186.73 New	N: nitrile rubber oil-resistant	50011	238			7.31 / 8.07	-	51.3	22	6	8
16.194.41	-	-	401	232			8	-	44.6	13	6	5
16.194.06	16.185.06 New	GT: gasket + cap	301	106			14.29 / 16	-	65	50.2	8	11
16.194.26	16.185.26 New	T: cap	301	114			14.29 / 16	-	65	50.1	10	20
16.194.07	-	GT: gasket + cap	901	105			22.5 / 25.4	-	96	63.1	9	13
16.194.08	-	GT: gasket + cap	801	145			22.5 / 25.4	-	95	88.5	12	15

Accessories: G: gasket. GT: gasket + cap. GX: gasket + nut. X: nut. CGT: key + gasket + cap. N: oil-resistant nitrile rubber. T: cap.