

#### New Edge hose connector/water hook-up with hot/cold water mixer

With female plug-in connector (standard international sizes) + hot/cold water single-control mixer (17.051.00).

white	Chromed	←	←→  <sub>mm</sub>		
	em omea	recess	outside	mixer	
16.442.70	16.442.71	148x74x40	180x106	17.051.00	







# OSCULATI



## New Edge recess fit fresh water inlet

When using the mains water supply, pressure can be reduced by up to 3 bar to prevent damage to the pipes. The hose **snaps in using a garden-hose adaptor** (see code 36.189.02). 3/4" thread male outlet.

white	chromed	<b>■</b> ss	←→  <sub>mm</sub>		
			Ø Recess	Internal protrusion	90° fitting
16.441.14	16.441.34	16.441.84	69	90/120	Included









# CISCULATI



#### Heavy Duty New Edge recess-fit hose connector for fresh water

## QUICK SWIVEL CONNECTION

## PRESSURE REDUCING VALVE

Ideal when you want to use quayside fresh water: it reduces the pressure to 3 bars not to damage the pipes by means of an innovative compact system fitted with adjustable pressure regulator and brass check valve. The quayside water pipe snaps into a gardening-like hose connector (see code 36.189.02). BSP male 3/4" outlet thread.

The dock water pipe snaps into place via a gardening-type fitting (code 36.189.02). 3/4" BSP outlet thread.

white	chromed	<b> ■</b> ss	←→  <sub>mm</sub>		
			Ø Recess	Internal protrusion	
16.445.14	16.445.34	16.445.84	69	110-110	









# **OSCULATI**



#### Classic Evo recess-fit fresh water inlet

When using the mains water supply, pressure can be reduced by up to 3 bar to prevent damage to the pipes. The hose snaps in using a garden-hose adaptor (see code 36.189.02). 3/4" thread male outlet.

white	chromed	<b>E</b> ss	←→  <sub>mm</sub>		
			Ø Recess	Internal protrusion	90° fitting
16.441.53	16.441.73	16.441.83	69	97/125	Included











# OSCULATI

