

LEWMAR'





LEWMAR HX1 GO windlass kit, 500W and 800W

The HX range offers a completely new project both inside and outside: the result is a new, robust and reliable windlass with in-line motor and worm wheel gearbox.


The HX features an aluminium frame designed to withstand years of heavy loads. The covers are

2 options to choose as Gypsy: 6/7 mm or 8 mm, motors of 500 and 800 W.

Waterproof unit IP67.

Quiet under load.


A manual 'free fall' kit is available to be applied over the sprocket.



Winch complete with external unit, motor, remote switch and gypsy	Motor		Gyp	Pull kg		Line speed m/min		Current	Recommended	For boats		OPTIONAL HX1	
	٧	w	chain Ø mm	Line Ø mm	max	continuous	max	continuous	draw A	circuit breaker A		o kg	free release kit
02.605.06	12	500	6	12-16	700	175	20	5	75	70	6 to 9 m	9.5	02.606.99
02.606.06	12	800	6	12-16	1065	267	21	5	105	90	9 to 13 m	9.5	02.606.99
02.606.08	12	800	8	12-16	1065	267	21	5	105	90	9 to 13 m	9.5	02.606.99


LEWMAR Series VX Stainless Steel Anchor Winches and Spare Parts

LEWMAR



LEWMAR VX1 GO windlass kit, 300W and 500W

- Stainless steel construction and composite details.
- Patent-pending sturdy hybrid gypsy, very silent, lightweight and suitable for rope/chain.
- Fitted with magnet and chain counter sensor.
- Manual clutch release.
- Same footprint as V1 model.
- robust helical reducer;
- IP67 certified motor gearbox.
- Solenoid included.
- Easy to adjust and install.



Winch complete with external unit motor, remote switch and gypsy		otor	Gyp	P	Pull kg	Line s _l	peed m/min	Current draw A	Recommended circuit breaker A	For boats	0	
motor, remote switch and gypsy	٧	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous	uraw A	Circuit breaker A		Kg.
02.590.06	12	300	6	12-16	400	100	25	6	66	50	6 to 9 m	12.5
02.591.06	12	500	6	12-16	675	169	25	6	126	70	6 to 9 m	12.5
02.591.08	12	500	8	12-16	675	169	25	6	126	70	6 to 9 m	12.5

LEWMAR





LEWMAR VX2 GD/GO windlass kit, 700W

- Stainless steel construction and composite details.
- Certified sturdy hybrid gypsy, very silent, lightweight and suitable for rope/ chain.
- Fitted with magnet and chain counter sensor.
- Manual clutch release.
- Same footprint as V2 model.
- robust helical reducer;
- IP67 certified motor gearbox.
- Solenoid included
- Easy to adjust and install.
- available in a version with gypsy and bell.

Windlass with deck unit, motor gearbox, solenoid and gypsy	Version	Motor		Gypsy		Pull kg		Line speed m/min		Current	Recommended		For boats
	version	٧	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous	draw A	circuit breaker A	c kg	1 of boats
02.593.06	GO	12	700	6	12-16	850	212	29	7	120	90	13.9	9 to 12 m
02.593.08	GO	12	700	8	12-16	850	212	29	7	120	90	13.9	9 to 12 m
02.594.06	GD	12	700	6	12-16	850	212	29	7	120	90	14.9	9 to 12 m
02.594.08	GD	12	700	8	12-16	850	212	29	7	120	90	14.9	9 to 12 m

