# Check valves

### Non-return valve to be installed along diesel pipelines

| Code | for pipe Ø mm |
|---|---|
| **17.731.90** | 8 |
| **17.731.91** | 10 |
| **17.731.92** | 12 |

### Check valve

Made of polypropylene with internal rubber flapper; hose adapter; multipurpose valve, use to let water flow in just one direction.

| Code | Multiple hoseholder in mm |
|---|---|
| **17.176.53** | 13/20/26 |
| **17.176.54** | 25/32/38 |

### Multiple hose connector with check valve

With quick connection system.

| Code | Hoseholder in mm |
|---|---|
| **17.176.56** | 13/20/26 |
| **17.176.57** | 25/32/38 |

### WHALE in-line check valve

Polypropylene body and nitrile valve. Duckbill valve.

| Code | Hoseholder in mm | Version |
|---|---|---|
| **17.121.50** | 25/38 | Universal |
| **17.121.90** | 19/25 | Universal |



▲ 17.121.50   ▲ 17.121.90

Flow In — Flow Out — Check Valve Orientation

### Check valves

Made of **brass**, designed for mounting along pipework, prevents the backflow of fluids.

| Code | Thread |
|---|---|
| **17.232.02** | 1/2" |
| **17.232.03** | 3/4" |
| **17.232.04** | 1" |
| **17.232.05** | 1" 1/4 |
| **17.232.06** | 1" 1/2 |

# Quick couplings for hydraulic systems

### KP 12-mm Ø quick couplings for plumbing

Instant snap-in mounting. It requires a simple pressure of the tube and a fastening clip to connect the coupling. Fully re-usable joints made of non-toxic high-resistance food plastic and semi-rigid polyethylene pipe.

| Product description | 12-mm Ø | ORDER BY BOX |
|---|---|---|
| Manicotto di collegamento femmina/femmina | **17.111.01** | 10 |
| 90° female/female elbow | **17.111.02** | 10 |
| 90° female tee | **17.111.03** | 10 |
| 3/8" female + female fitting | **17.111.04** | 10 |
| 1/2" female + female fitting | **17.111.05** | 10 |
| 3/8" female + male fitting | **17.111.06** | 10 |
| 1/2" female + male fitting | **17.111.07** | 10 |
| Cylinder joint + 3/8" male joint | **17.111.08** | 10 |
| Cylinder joint + 1/2" male joint | **17.111.09** | 10 |
| Female Y joint | **17.111.10** | 10 |
| In-line joint | **17.111.12** | 10 |
| 90° female joint with fitting | **17.111.14** | 10 |
| 90° female joint with 3/8" male joint | **17.111.13** | 10 |
| Intermediate lever tap | **17.111.19** | 1 |
| Safety clips | **17.111.35** | 10 |

◄ 17.111.01   ▲ 17.111.02   ▲ 17.111.03
◄ 17.111.04   ◄ 17.111.05   ◄ 17.111.06
◄ 17.111.07   ▲ 17.111.08   ▲ 17.111.09
◄ 17.111.10   ▲ 17.111.12   ▲ 17.111.13
◄ 17.111.14   ▲ 17.111.19   ▲ 17.111.35

17.111.01   17.111.02   17.111.03   17.111.04/05   17.111.06/07
17.111.08   17.111.09   17.111.10   17.111.13   17.111.14