

## 15-mm Ø quick-release couplings for WHALE hydraulic systems



**Main features:** exclusive "double seam" design that ensures a secure coupling even under sudden pressure changes, fitted with coupling close to the pipe elbows; does not require a safety clip, thus saving costs and installation time; pipe control marking to ensure a correct coupling; easy to use, does not require expert users for the installation; can be fixed and released without tools or replacement parts; maximum pressure at 20° 12 BAR / maximum pressure at 65° 6 BAR.

**Suitable for 15-mm Ø pipes.**

<div>WHALE T-joint</div> <div></div> <div>Code 17.815.02</div>	<div>WHALE elbow</div> <div></div> <div>Code 17.815.03</div>	<div>WHALE straight fitting</div> <div></div> <div>Code 17.815.04</div>																		
<div>WHALE BSP 1/2" male adapter</div> <div></div> <div>Code 17.815.14</div>	<div>WHALE T-fitting</div> <div></div> <div>Code 17.815.21 This joint coupled together can turn into a clarinet with adjustable outflow.</div>	<div>WHALE fused elbow</div> <div></div> <div>Code 17.815.22</div>																		
<div>WHALE BSP 1/2" male adapter</div> <div></div> <div>Code 17.815.32</div>	<div>WHALE BSP 1/2" female adapter (brass)</div> <div></div> <div>Code 17.815.33</div>	<div>WHALE shut-off valve (brass)</div> <div></div> <div>Code 17.815.75</div>																		
<div>WHALE 3/8" BSP male adapter</div> <div></div> <div>Code 17.815.83</div>	<div>WHALE adaptor size 3/8 BSP female (plastic)</div> <div></div> <div>Code 17.815.39</div>	<div>WHALE adaptor size 3/4" BSP female</div> <div></div> <div>Code 17.815.40</div>																		
<div>WHALE cylindrical joint + male 1/2 BSP</div> <div></div> <div>Code 17.815.87</div>	<div>WHALE Cylindrical joint for 12-mm hose</div> <div></div> <div>Code 17.815.84</div>	<div>WHALE cylindrical joint for flexible pipe size 16 mm</div> <div></div> <div>Code 17.815.97</div>																		
<div>WHALE cylindrical joint for flexible pipe size 20 mm</div> <div></div> <div>Code 17.815.93</div>	<div>WHALE cylindrical elbow joint for flexible pipe size 20 mm</div> <div></div> <div>Code 17.815.92</div>	<div>WHALE shut-off valve</div> <div></div> <div>Code 17.815.74</div>																		
<div>WHALE elbow with thread size 1/2 BSP female</div> <div></div> <div>Code 17.815.31</div>	<div>WHALE brass plug</div> <div></div> <div>Code 17.815.08</div>	<div>WHALE plug</div> <div></div> <div>Code 17.815.46</div>																		
<div>WHALE check valve</div> <div></div> <div>Code 17.815.82</div>		<div>WHALE cold water pipe</div> <div></div> <table><tr><th>Code</th><th>tube in mm</th><th>Colour</th><th>Roll m</th></tr><tr><td>17.815.52</td><td>15</td><td>Blue</td><td>50</td></tr></table>	Code	tube in mm	Colour	Roll m	17.815.52	15	Blue	50										
Code	tube in mm	Colour	Roll m																	
17.815.52	15	Blue	50																	
<div>WHALE hot water pipe</div> <div></div> <table><tr><th>Code</th><th>tube in mm</th><th>Colour</th><th>Roll m</th></tr><tr><td>17.815.54</td><td>15</td><td>Red</td><td>50</td></tr></table>		Code	tube in mm	Colour	Roll m	17.815.54	15	Red	50	<div>Stainless steel braided pipe suitable for water heating connections</div> <div></div> <table><tr><th rowspan="2">Code</th><th rowspan="2">Length cm</th><th colspan="2">Thread</th></tr><tr><th>No. and type</th><th>Fittings</th></tr><tr><td>50.289.56</td><td>45</td><td>1 (male) + 1 (female)</td><td>1/2"</td></tr></table>	Code	Length cm	Thread		No. and type	Fittings	50.289.56	45	1 (male) + 1 (female)	1/2"
Code	tube in mm	Colour	Roll m																	
17.815.54	15	Red	50																	
Code	Length cm	Thread																		
		No. and type	Fittings																	
50.289.56	45	1 (male) + 1 (female)	1/2"																	