LEWMAR

LEWMAR VX1L low/high winch kit (500 W and 800 W)

IP67

Same features of the VX range, it frees below deck storage space.
Fitted with efficient in-line motor and robust worm wheel gearbox.
2 models available as gypsy: 6/7mm and 8mm. Motor range 500 and 800W, IP67 cover.

- **Pre-installed magnet and chain counter sensor.**
- **Solenoid included.**
- **Manual clutch release.**
- **Stainless steel and composite construction.**





Winch complete with external unit, motor, remote switch and gypsy	Version	Motor		Gypsy		Pull kg		Line speed m / min		Current draw A	Recommended circuit breaker A	For boats	kg
		V	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous				
02.603.06	GO	12	500	6	12-16	650	160	20	5	75	70	6 to 9 m	8.5
02.604.06	GO	12	800	6	12-16	920	230	21	5	105	90	9 to 13 m	8.5
02.604.08	GO	12	800	8	12-16	920	230	21	5	105	90	9 to 13 m	8.5
02.610.08	GD	12	800	8	12-16	920	230	21	5	105	90	9 to 13 m	8.5

Spare parts series VX and VXL

Code	Description
02.590.07	12V watertight remote control switch
02.590.08	Lewmar toggle switch with protection
02.590.10	VX windlass chain cover and control arm
02.590.12	VX1 12V 500W gearmotor IP67 RMU40
02.590.14	VX2/3 chain cover kit
02.590.16	VX2/3 manual conversion kit
02.590.18	Manual recovery for VX2/3 low
02.590.20	VX2 12V 700W gearmotor IP67 RMU50
02.590.22	VX2 12V 1000W gearmotor IP67 RMU50
02.590.96	VX1/VX1L 6/7mm gypsy
02.590.98	VX1/VX1L 8mm gypsy
02.593.80	VX2/3 10mm gypsy kit, DIN766
02.593.90	VX2/3 10mm gypsy kit, ISO
02.593.96	VX2/3 7mm gypsy kit
02.593.98	VX2/3 8mm gypsy kit

LEWMAR V-Series stainless steel windlasses

Windlasses for pleasure boating made with a precision-cast stainless steel deck unit. Modern look and excellent quality material.

LEWMAR

FALL SAFE

LEWMAR V1 GO windlass, 700W

AISI 316

FAST FIT

FALL SAFE

- Rope/chain gypsy.
- AISI316 stainless steel deck unit.
- FastFit: new patented motor mounting option for quicker installation.
- Fall Safe anchor lock.
- Modern design.
- Sold in pack including switch, solenoid, circuit breaker and clutch release lever.
- ready to fit chain counter sensor.
- IP68 waterproof unit.

Code	Motor		Gypsy		Pull kg		Line speed m / min		Current draw A	Recommended circuit breaker A	Only gypsy	For boats	kg
	V	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous					
02.535.06	12	700	6	12-14	454	113	19	13	80	90	02.519.06	7 to 12 m	16.5
02.535.08	12	700	8	12-16	454	113	19	13	80	90	02.519.08	7 to 12 m	16.5



Flat view



Motor and gearbox unit