

Electrovalves

Electro-valve

Made in compliance with Directive EMC 2014/30/EU (EN 6100-6-3:2007+A1:2011). It enables the electrically-operated control to intercept fuel delivery from a remote position. Also fitted with manual control.

Complete with nipples for rubber hose 8/10 mm, fitting for copper pipe 10 mm and mounting plate with bolts. IP65.

Code	Material	Power V	Maximum capacity l/h	At constant pressure l/h
17.403.00	Brass	12	200	100
17.403.01	Brass	24	200	100



OSCULATI




CE

Electro-valve for fuel

Allows remote interception of fuel dispensing with electronic control
Equipped with a manual emergency control.

Code	Material	Power V	Maximum capacity l/h	At constant pressure l/h	Hose adaptor	Weight
17.401.12	Brass	12	800	400	1/2"	570
17.401.24	Brass	24	800	400	1/2"	570



OSCULATI



CE

PAOMAR electro-valve

Compliant with Directive 2013/53/EU (ISO 8846 MARINE - EN 28846) for fuel interception, patented PAOMAR. [Technical Data](#)

- 1) Remote electric control with emergency manual handle.
- 2) Flow rate **600 litres/hour** at 0.2 bar, thus suitable for any engine (even with modest displacement, as they require 3-4 times the fuel consumed at standard operation during acceleration).
- 3) Non-contact fuel control mechanism. 100% seal guaranteed even after years of use, with no "O Rings" or sliding elements.
- 4) Equipped with new universal 12/24 volt connector with power-saving electronic circuit.
- 5) Operation indicator LED.
- 6) Protection against polarity reversal.
- 7) Electronic circuit with holding impulse, which ensures operation in case of accidental release of the solenoid valve.
- 8) Ability to mount various types of fittings, complete with stainless steel bracket for installation in various positions.

Code	Power V	Fitting for copper pipe 8x10 mm	Fitting for copper pipe 10x12 mm	Rubber hose fitting 10x21 mm
17.402.12	12	17.408.04	17.402.51	17.402.60
17.402.24	24	17.408.04	17.402.51	17.402.60

OSCULATI



CE

Petrol and diesel fuel filters

Plastic transparent filters

Suitable for both petrol (E5 - E10 - E15) and diesel.

Code	Type	Max. flow rate l/h	Hose adaptor mm
17.658.00	small	50	6 - 8
17.658.01	Large	150	8 - 10



Petrol filter for flush mounting on pipeworks

Body made of **chromed zamak and clear shatter-proof glass**; the user can see the fuel and any possible filter saturations; removable, fitted with replaceable refill filter; includes 3 hose adaptors sizes 6/8/10, designed to fit into any type of piping.

Code	Length mm	3 spare refill
17.665.00	28x85	17.665.01

