



Purifying filter for diesel fuel with clear tray

Made of die-cast aluminium, with clear polycarbonate tray and bottom drain screw.

Code	Flow rate l/h		Filter in washable stainless steel mesh	←→ mm	Over-hang mm	Hose holder MB	Hose adaptor	Spare cartridge
	maximum	optimal						
17.639.00	400	130	200 micron	150x80	65	14	17.660.02; 17.660.03; 17.638.02; 17.638.03	17.639.01



Fuel filter with clear glass tray

With easily removable tray for filter cartridge replacement. Particularly suitable for outboard engines.

Code	Version	OPTIONAL fittings	Flow rate l/h		←→ mm	Spare cartridge
			optimal	max		
17.656.00	With 200-micron S.S. filtering cartridge, washable	17.660.02; 17.660.03; 17.638.02; 17.638.03	50	250	110x75x60 (compact)	17.656.01 stainless steel
17.656.05	With 12-micron paper filtering cartridge	17.660.02; 17.660.03; 17.638.02; 17.638.03	20	150	110x75x60 (compact)	17.656.07 chart



Purifying filter for diesel fuel, made of die-cast aluminium

Fitted with interchangeable cartridge, maximum capacity of 65 l/hour, lower unblocking, filtering level of 12 micron.


Code	Flow rate l/h	Maximum external dimension mm	Thread MB	Spare cartridge	Lower cup in	OPTIONAL fittings
17.661.15	65	160x100x92	14	17.666.10	Glass to see possible residues of water or other materials	17.660.02; 17.660.03; 17.638.02; 17.638.03



Purifying filter for diesel fuel

Made of die-cast aluminium; fitted with hand pump for filling the circuit (5 threaded holes + 3 plugs).

Code	Flow rate l/h	Maximum external dimension mm	Thread MB	OPTIONAL fittings	Spare cartridge
17.842.10	65	160x100x92	14	17.660.02; 17.660.03; 17.638.02; 17.638.03	17.666.10



12-micron paper filter for diesel fuel

Made of die-cast aluminium; fitted with separator cartridge (screwed in); bottom drain screw.

Code	Max. flow rate l/h	Filtration grade	Thread MB	Maximum external dimension mm	OPTIONAL fittings	Spare cartridge
17.638.00	80	12 micron	14	200x113x91	17.660.02; 17.660.03; 17.638.02; 17.638.03	17.638.01



17.661.40



17.661.60

Water-fuel filter/separator

Made of anodized aluminium, with transparent container that can be taken off to clean it or to replace the filtering cartridge.

Code	Filter	Filtration grade	Water drain screw	Flow rate l/h with pressure			Height mm	Ø cartridge mm	Hose holder included 11/16" UNC	Spare cartridge
				0.49 PSI	1.5 PSI	2.45 PSI				
17.661.40	petrol	10 micron	Yes	205	333	420	190	110	2 x 10 mm	17.661.50
17.661.60	Gasoil	25-micron	Yes	205	333	420	190	110	2 x 10 mm	17.661.70