

Diesel filter type CAV with water drain

Water-fuel filter separator. Made in compliance with the ISO 10088 standard. Aluminium head and water drain container.

Code	Type	Flow rate l/h		Thread MB mm	↔ mm	Spare cartridge	OPTIONAL fittings
		optimal	max				
17.666.00	296	50	100	14	175x100	17.666.10*	17.660.02/03; 17.638.02/03
17.666.01	396	60	130	14	220x100	17.666.11	17.660.02/03; 17.638.02/03

* Equivalent Volvo 858201-3581078



17.666.10



17.666.11

OSCULATI



17.666.00



17.666.01

Filter + water/fuel separator with 10 micron cartridge

Composite technopolymer head, transparent tank with quick drain. Complete with hose holder (two 10 mm, two 8 mm). For outboard engines.

Code	Flow rate l/h with pressure			Total height mm	Overhang mm	Ø mm	Replacement cartridge 10 microns
	0.49 PSI	1.47 PSI	2.45 PSI				
17.661.33	200	316	406	190	85	68	17.661.34



Universal water/fuel separator filter

OSCULATI

With aluminium support and standard cartridge. Fitted with conical, self-locking and self-sealing hose adaptors.

Code	Micron Cartridge	Suitable for	Water collection tray		Drain plug	Total height mm	Ø mm	Overhang mm	Flow rate l/h with pressure			Cartridge thread	Fittings included	Spare cartridge
			Material	Replacement					0.49 PSI	1.47 PSI	2.45 PSI			
17.664.00	10	petrol/diesel	Clear polyamide	17.664.12	Black plastic	220	93	100	192	324	410	11/16"	2 x 10-mm Ø hose connectors	17.664.10
17.664.03	30	Diesel	Aluminium	-	Chromed brass	220	93	100	192	324	410	11/16"	2 x 10-mm Ø hose connectors	17.664.11



17.664.10 Replacement RACOR S3213/Mercury/Mercuriser/Volvo/Yamaha/Suzuki/Sierra.



17.664.00 Black plastic bleed cap



17.664.03 Drain plug in chromed brass



17.664.10



17.664.12



Racor equivalent spare cartridge

Code	Thread	Micron	Equivalence	Replacement tray
17.664.10	11/16"-16	10	RACOR S3213 (Volvo/Mercury 35-809097/Yamaha MAR-24563-00-00/Suzuki)	17.664.12
17.664.21	1"-14	10	RACOR S3227 (Honda 17670-ZW1-801AH/Mercury 35-886638/Suzuki 99105-20005)	17.664.12

