

OSCULATI**10-micron gasoline/diesel filter with disposable cartridge**

Fitted with conical, self-locking and self-sealing hose adaptor.

Code	Headrest	Height mm	Overhang mm	Ø cartridge mm	Cartridge thread	Flow rate l/h with pressure			Fittings 10 mm	Spare cartridge
						0.49 PSI	1.47 PSI	2.45 PSI		
17.660.40	Plastic	145	110	92	11/16"	182	315	404	INCLUDED	17.660.45
17.660.41	Aluminium	145	110	92	11/16"	182	315	404	INCLUDED	17.660.45

Equivalent Mercury 35-60494A4, 35-802893Q, 35-807172



17.660.45

OSCULATI

17.661.32

Petrol filter + water/fuel separator with 10 micron cartridge

Aluminium head, transparent tank, rapid drain system. Recommended for engines up to 200 HP - Equivalent to Yamaha 2W-114-00-00. Fitted with 8-mm hose adaptor.

Code	Flow rate l/h with pressure			Total height mm	Overhang mm	Ø mm	Replacement water collection tray	Cartridge thread	Ø hoseholder mm INCLUDED	Replacement cartridge 10 microns
	0.49 PSI	1.47 PSI	2.45 PSI							
17.661.30	200	316	406	230	90	75	17.661.32	13/16"	2 x 8	17.661.31

Equivalent Yamaha MAR - MINIF - IL - TR

Water-fuel filter/separator**OSCULATI**

Fitted with 10-micron high-capacity cartridge. Aluminium head. Universal size to fit any type of engine. Fitted with conical, self-locking and self-sealing hose adaptors, caps to close unused passages, and stainless steel clamps.

Code	Flow rate l/h with pressure			Micron Cartridge	Suitable for	Water collection tray		Drain plug	Total height mm	Ø mm	Overhang mm	Cartridge thread	Fittings included	Spare cartridge
	0.49 PSI	1.47 PSI	2.45 PSI			Material	Replacement							
17.661.35*	206	331	414	10	petrol/diesel	Aluminium	-	Chromed brass	280	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.26
17.661.24	206	331	414	10	petrol/diesel	Clear polyamide	17.664.12	Plastic	290	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.26
17.661.37	206	331	414	30	Diesel	Aluminium	-	Chromed brass	280	92	110	11/16"	2 x 10-mm Ø hose connectors	17.661.28

* Equivalent Yamaha MAR - FUELF - IL - TR



17.661.24 Black plastic vent cap



17.661.35/37 Chrome-plated brass vent cap



17.664.12

**Purifying filter fitted with stainless steel 120 micro filtering element**

Suitable for mid power motors; made in accordance with RINA standards, suitable for diesel or petrol.

Code	Fittings from	Maximum flow rate l/h (during acceleration)	Optimal pruning capacity l/h	100x100x235 mm	Spare cartridge
17.020.00	3/8"	460	240	100x100x235	17.020.01