




▲ 17.504.11



▲ 17.504.22

MERCURY outboard fuel filter

For Mercury VERADO 4/6 cylinder engines (Orig. 35-8M0020349 / 35-893318502).

Code	←→			Ref. Orig.	Engines
	Ø thread mm	Ø body mm	Height mm		
17.504.22	11	27	45	35-8M0168897	75/115 HP 4 Strokes
17.504.11	45.5	35.5	126	35-8M0122423; 35-8M-0020349; 35-8843801	4/6 cylinders Verado



▲ 17.504.28



▲ 17.504.29

Outboard fuel filter Yamaha Suzuki

Code	Orig. Ref.		Engines	
	Yamaha	Suzuki	Yamaha	Suzuki
17.504.28	6D8-WS 24A-00	15412-92J00	F30/40/50/60/70/75/90/F115-LF115	70/200 HP 4 strokes
17.504.29	6P3-WS 24A-01	15412-93J10	F30/40/50/60/70/75/90/F115-LF115	200/350 HP 4 strokes

**Universal key to screw/unscrew strainers**

Code 17.640.00


It can be used with both fuel and oil strainers. It screw/ unscrew the clear or light alloy trays of water/ fuel separator strainers.

Fuel and water pipes**Copper pipe designed for fuel or liquid gas inflow**

Meets with Directive ISO7840/10088/16147DIS for fuel and 10239 liquid gas.

Code	←→ mm	Roll m
45.028.11*	6 x 8	50
45.028.10	8 x 10	50
45.028.12	10 x 12	50

* Particularly suitable for gas.



▲ 17.751.08/10/12/16/19



▲ 17.751.25/38/40/50/60

Smooth pipe for fuel

Made in compliance with EC standards, RINA ISO 7840/2013 type-tested under class **A1** (the lower class A2, is **not** allowed for petrol, but only for diesel fuel). Synthetic fabric reinforcement. Smooth fabric-like surface.

Code	Section mm	Inside Ø mm	External Ø mm	Weight per meter g/m	Curvature radius mm	Roll m
17.751.08	8 x 17	8	17	0.27	50	40
17.751.10	10 x 19	10	19	0.30	60	40
17.751.12	12 x 21	12	22	0.43	75	40
17.751.16	16 x 26	16	26	0.50	100	40
17.751.19	19 x 29	19	30	0.64	115	40
17.751.25	25 x 35.5	25	37	0.87	250	20
17.751.38	38 x 52	38	52	1.55	380	10
17.751.40	40 x 54	40	54	1.60	400	10
17.751.50	50 x 64	51	65	1.95	500	10
17.751.60	60 x 71.5	-	-	-	-	10

Metal spiral pipe for fuel

Made in compliance with EC standards, RINA ISO 7840/2013 type-tested under class **A1**, **flexible** version also for large diameters. Double metal spiral reinforcement. Ondulated surface.

Code	Section mm	Minimum bend radius mm	Inside Ø mm	Weight per meter g/m	Roll m
17.752.38	38 x 50	60	38	1.05	10
17.752.50	50 x 63	75	51	1.35	10

**Hot Water pipe made of special salt water- and heat-resistant rubber (-40°+120°)**

Designed for cooling systems, heat exchange systems and boilers. Synthetic fabric reinforcements. Smooth surface.

Code	Section mm	Approximate weight kg/m	Roll m
17.740.13	12.8 x 20	0.36	40
17.740.16	15.8 x 23	0.42	40
17.740.19	19 x 27	0.48	40
17.740.26	25 x 34	0.62	40
17.740.30	30 x 42	0.80	20
17.740.35	35 x 49	1.10	20
17.740.40	40 x 54	1.33	10
17.740.50	51 x 66	1.80	10

