

LEWMAR



▲ V4 low




▲ High V4

LEWMAR V4 GD/GO windlass, 1600W and 2000W**AISI 316**

Gypsy and chain; deck unit in stainless steel 316;
Modern look; prepared for chain counter sensor. Waterproof unit IP68.

PATENT

▲ Flat view



▲ Deck unit

Winch complete with external unit, motor, remote switch and gypsy	Version	Motor		Gypsy		Pull kg		Line speed m/min		Current draw A	Recommended circuit breaker A	For boats	kg	Single parts			
		V	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous					Only gypsy	Only solenoid	Only motor/gear-box	Only deck unit
02.557.08	GO	12	1600	8	12-14	1250	313	25	15	125	150	13 to 16 m	28	02.529.08	02.590.03	02.525.12	02.522.01
02.557.10	GO	12	1600	10	16	1250	313	25	15	125	150	13 to 16 m	28	02.529.10	02.590.03	02.525.12	02.522.01
02.558.08	GD	12	1600	8	12-14	1250	313	25	15	125	150	13 to 16 m	30	02.529.08	02.590.03	02.525.12	02.522.02
02.558.10	GD	12	1600	10	16	1250	313	25	15	125	150	13 to 16 m	30	02.529.10	02.590.03	02.525.12	02.522.02
02.560.08	GO	24	2000	8	12-14	1500	375	27	16	70	110	13 to 16 m	28	02.529.08	02.590.04	02.525.24	02.522.01
02.560.10	GO	24	2000	10	16	1500	375	27	16	70	110	13 to 16 m	28	02.529.10	02.590.04	02.525.24	02.522.01
02.561.08	GD	24	2000	8	12-14	1500	375	27	16	70	110	13 to 16 m	30	02.529.08	02.590.04	02.525.24	02.522.02
02.561.10	GD	24	2000	10	16	1500	375	27	16	70	110	13 to 16 m	30	02.529.10	02.590.04	02.525.24	02.522.02

LEWMAR



▲ Low V5




▲ V5 high

LEWMAR V5 GD/GO windlass, 2000W**AISI 316**

- Rope/chain gypsy.
- AISI316 stainless steel deck unit.
- Modern design.
- ready to fit chain counter sensor.
- IP68 waterproof unit.

PATENT

▲ Flat view



▲ Deck unit

Winch complete with external unit, motor, remote switch and gypsy	Version	Motor		Gypsy		Pull kg		Line speed m/min		Current draw A	Recommended circuit breaker A	For boats	kg	Single parts			
		V	W	chain Ø mm	Line Ø mm	max	continuous	max	continuous					Only gypsy	Only solenoid	Only motor/gear-box	Only deck unit
02.562.10	GO	24	2000	10	16	1600	400	29	18	60	110	15 to 18 m	32	02.529.10	02.590.02	02.526.24	02.522.01
02.562.12	GO	24	2000	12	18-20	1600	400	29	18	60	110	15 to 18 m	36	02.529.12	02.590.02	02.526.24	02.522.01
02.563.10	GD	24	2000	10	16	1600	400	29	18	60	110	15 to 18 m	34	02.529.10	02.590.02	02.526.24	02.522.02
02.563.12	GD	24	2000	12	18-20	1600	400	29	18	60	110	15 to 18 m	38	02.529.12	02.590.02	02.526.24	02.522.02

**LEWMAR****LEWMAR V6 Low/High Winch (2000 W)****AISI 316**

- High-power worm gearbox.
- Modern design.
- AISI316 stainless steel deck unit.
- ready to fit chain counter sensor.
- IP68 waterproof unit.

PATENT

Winch complete with external unit, motor, remote switch and gypsy	Version	Motor		Gypsy Ø chain mm	Pull kg		Line speed m/min		Current draw A	Recommended circuit breaker A	For boats	kg	Single parts			
		V	W		max	continuous	max	continuous					Only gypsy	Only solenoid	Only motor / gearbox	Only deck unit
02.565.12	GD	24	2000	12	1850	455	18	4.2	90	150	16 to 22 m	55	02.539.12	02.590.04	02.536.24	02.533.02
02.565.14	GD	24	2000	14	1850	455	18	4.2	90	150	16 to 22 m	55	02.539.14	02.590.04	02.536.24	02.533.02
02.566.12 New	GO	24	2000	12	1850	455	18	4.2	90	150	16 to 22 m	55	02.539.12	02.590.04	02.536.24	02.533.04
02.566.14 New	GO	24	2000	14	1850	455	18	4.2	90	150	16 to 22 m	55	02.539.14	02.590.04	02.536.24	02.533.04

